

Full Body Harnesses

Front



No. 6176K Pro-Arc-Flash Dielectric Flame Resistant Arc-Flash Harness

Full body harness 3rd party certified to pass the ASTM arc flash test and dielectric connector rating. Built with flame resistant webbing and nylon insulated connectors. Specified for use where electrical hazards, arc flash or other sources of ignition are present. Suitable for welding.

- Universal Size adjusts 140-310lb.
- 100% Dielectric connectors 13kV voltage rating.
- Flame resistant webbing
- 1 dorsal and 2 side D-rings
- Fall indicator labels
- Inspection label
- 3rd party Arc-Flash testing meets ASTM F887-13 Certificate upon request
- Complies with ANSI Z359.11-14 for fall arrest use

Pkg, Wt. 4.5 lb

Back



Front



No. DE-6001K Harness with Dielectric Connectors

Full body harness fitted with dielectric connectors. Mfg. with our most popular high visibility polyester webbing. Specified for use where electrical hazards or corrosive chemicals may come in contact with connectors.

- Universal Size adjusts 140-310lb.
- 100% Dielectric connectors 13kV voltage rating.
- 1 dorsal D-ring
- Fall indicator labels
- Inspection label
- Complies with ANSI Z359.11-14 for fall arrest use

Pkg, Wt. 3.0 lb