

# Horizontal Lifeline Kits

## No.1321 20'ft 5° Horizontal Lifeline System w/Metallic Energy Absorber Mfg. at Super Anchor Safety Factory in Monroe, WA USA

Specified for use on wood framed structures. Installs with duplex nails or #12 hex head wood screws.  
One end of the horizontal lifeline – is factory attached to the Hinge 2 anchor, the other end is bolt attached to the metallic energy absorber.

Pkg, Wt. 18 lb

### Certification/Compliance

3rd party certified by a member of  
l'Ordre des ingénieurs du Québec.

### User Specifications:

- 2 person Fall Arrest
- 3 person Fall Restraint

### Kit Specifications:

- 2 ea. Hinge Anchors No. 3006
- No.1059 stainless steel Metallic Energy Absorber with tension gauge and fall indicator and grade 8 attachment bolts
- 20ft length 5° angle lifeline 14,400lb (64kN) tensile strength 7x19x3/8" galvanized wire rope w/double swagged terminations and clear PVC covers
- 3 Connector rings
- 2ea 36pack 16d duplex nails
- English/Spanish Instructions Product ID and Inspection labels



## No.1322 Horizontal Lifeline Kit

Kit No.1321 supplied with a large size cargo bag for easy transport and storage.

Pkg, Wt. 20lbs

