

MAX Force™ Energy Absorbers

No. 6196-C
Stainless Steel

No. 6196-Z
Zinc Plated Steel

No. 6196-M
Integral Adjuster



Carabiner No. 5006Z

- 5,395lb(24kN) min. tensile strength
- 22mm gate opening
- 3,600lb(16kN) gate strength
- Complies with ANSI-Z359.12 and CSA Z259.12

Integral Adjuster

- Complies with OSHA 1926.502 ANSI Z359.1-07
- Captive once installed
- Dual cam locking
- Compatible with all 5/8" synthetic lifelines.
- Most economical

Fall Arresters

- Complies with OSHA 1926:502/ANSI Z359.1-07
- Serial numbered
- Panic grab function
- Removable
- Single cam locking
- Compatible with all 5/8" synthetic lifelines



Standard Absorbers with Fall Arresters and Integral Adjusters Supplied with Aluminum Carabiners

Energy absorbers supplied with aluminum carabiners are 9oz lighter than energy absorbers with factory attached snaphooks and many users say they are more comfortable on your back. We use a very high quality twist lock self closing aluminum carabiner with high visibility red anodized coating. Mfg. at SAS factory in Monroe, WA USA

All models listed here have a user weight of 100-310lb

Model	A-end	B-end	wt/oz.
6196-C	Aluminum Carabiner	4015-C Fall Arrester	34
6196-M		4015-M Integral Adjuster	29
6196-Z		4015-Z Fall Arrester	34