

Anchors

Apex Ridge Top Anchor



OVERVIEW

This anchor was developed specifically for production builders and roofing companies. It is installed directly over the roof decking and can be nailed down by the framing or roofing contractor. It eliminates the need to install a temporary anchor for fall protection thus saving time and money. The unique design allows the roofer to “course under” the tie-off tab with a full course of roofing material – no more cutting or notching the shingle to accommodate your safety anchors. The next course of roofing covers the anchor leaving the tie-off tab exposed. This is the only anchor on the market that allows the roofer to literally roof under/over without interrupting his install.

2 anchor options are available: #2796 Ridge Mount anchor with 2 connector attachments and the #2793 with 1 attachment hole. The #2793 is designed to be installed on the hip-ridge or hip apex. The APEX is one of the lowest cost anchors available in the market. It is aesthetically pleasing and does not detract from the look of the roof. The APEX is powder coated in brown and blends in with all colors of roofing material. It can be painted to match the roofing color, too.

- Device:** Fall Arrest Anchor
- Material:** 11-gauge steel
- Coating:** Zinc Coat & Powder Coat
- Install Hardware:** 316 stainless steel nails
- Min. Tensile:** 5,000 pounds
- Fall Indicator:** Stem Deformation
- Working Radius:** Direction of Slope or Leading Edge
- Specification Use:** 1 person Fall Arrest
- Max Weight:** 310 pounds with tools
- Instruction Manual:** English/Spanish/French
- Engineering:** 3rd Party Certified
- Compliance:** OSHA 1926:502, 1910.66, ANSI Z359.1-07, A10.32-2012

