

# Commercial Anchors • CRO

## CRO Loop Top Anchor CAL-OSHA Compliant

CAL-OSHA window washing anchors are required to have zero deformation with a 5,000lb load applied to the loop top at any angle and the loop top must have a 2.0" min. i.d. Our CRO anchors and No.1093-1093-S loop tops are 3rd party certified to comply with CAL-OSHA Title 8 requirements. Choose from pre-engineered designs or custom fabrication.

- Min. Tensile Strength 5,000lb
- \*No.1093 and 1093-S 316 sst loop tops tensile strength rating of 10,000lb
- Stainless Steel vent hole plug
- Hot Dip Galvanized (HDG)
- 304 or 316sst
- Base Plate Options: 10x10/12x12/16x16
- Bolt Hole Options: 4-8 or 12 and diameter
- 3rd party engineering by DH Glabe

Sch 80=0.337

Sch XX=0.674



Use Rating	Riser Height	Part Name	Riser		12x12 Base Plate	Steel Type	SAS Part No.	Top Fixture	
			Sch	O.D.				No.	Type
<p><b>Rated For Window Washing</b></p> <p><b>1 Person PPE Anchor</b></p> <p><b>HLL End and Intermediate Anchors</b></p>	<b>8</b> △ △	CRO-8 38lb	80	4.5"	<b>5/8"</b>	HDG	1400-G	1093	Q345
						304sst	1400-S	1093-S	316sst
						316sst	1400-SX		
	<b>12</b> △ △	CRO-12 49lb	80	4.5"	<b>3/4"</b>	HDG	1401-G	1093	Q345
						304sst	1401-S	1093-S	316sst
						316sst	1401-SX		
	<b>18</b> △ △	CRO-18 66lb	80	4.5"	<b>1.0"</b>	HDG	1402-G	1093	Q345
						304sst	1402-S	1093-S	316sst
						316sst	1402-SX		
	<b>24</b> △ △	CRO-24 79lb	80	4.5"	<b>1-1/8"</b>	HDG	1403-G	1093	Q345
						304sst	1403-S	1093-S	316sst
						316sst	1403-SX		
<b>30</b> △ △	CRO-30 137lb	XX	4.5"	<b>1-1/4"</b>	HDG	1404-G	1093	Q345	
					304sst	1404-S	1093-S	316sst	
					316sst	1404-SX			
<b>36</b> △ △	CRO-36 158lb	XX	4.5"	<b>1-3/8"</b>	HDG	1405-G	1093	Q345	
					304sst	1405-S	1093-S	316sst	
					316sst	1405-SX			

△ Rated for Window Washing 5,000lb max. proof load.

△ Bolt attached, concrete embedment or field weld.

\*No.1093/S Loop Tops have a 7/8" loop diameter and are not compatible with some standard sized locking snap hooks. Use Steel or Aluminum auto-locking carabiners or rebar hooks.