

Commercial Anchors • CRR

CRR Field Welded Riser CAL-OSHA Compliant

CAL-OSHA window washing field welded risers are required to have zero deformation with a 5,000lb load applied to the loop top at any angle and the loop top must have a 2.0" min. i.d. Our CRR risers and No.1093-1093-S loop tops are 3rd party certified to comply with CAL-OSHA Title 8 requirements. Choose from pre-engineered designs or custom fabrication.



- Min.Tensile Strength 5,000lb
- *No.1093 and 1093-S 316 sst loop tops tensile strength rating of 10,000lb
- Stainless Steel vent hole plug
- Hot Dip Galvanized (HDG)
- 304 or 316sst
- 3rd party engineering by DH Glabe

Use Rating	Riser Height	Part Name	Material			SAS Part No.	Top Fixture	
			Wall	O.D.	Type		No.	Type
Rated For Window Washing 1 Person PPE Anchor HLL End and Intermediate Anchors	8 △	CRR-8 17lb	Sch 80 0.337	4.5"	HDG	1201-G	1093	Q345
					304sst	1201-S	1093-S	316sst
					316sst	1201-SX		
	12 △	CRR-12 24lb	Sch 80 0.337	4.5"	HDG	1202-G	1093	Q345
					304sst	1202-S	1093-S	316sst
					316sst	1202-SX		
	18 △	CRR-18 32lb	Sch 80 0.337	4.5"	HDG	1203-G	1093	Q345
					304sst	1203-S	1093-S	316sst
					316sst	1203-SX		
	24 △	CRR-24 39lb	Sch 80 0.337	4.5"	HDG	1204-G	1093	Q345
					304sst	1204-S	1093-S	316sst
					316sst	1204-SX		
	30 △	CRR-30 69lb	Sch XX 0.674	4.5"	HDG	1205-G	1093	Q345
					304sst	1205-S	1093-S	316sst
					316sst	1205-SX		
	36 △	CRR-36 83	Sch XX 0.674	4.5"	HDG	1206-G	1093	Q345
					304sst	1206-S	1093-S	316sst
					316sst	1206-SX		

△ Rated for Window Washing 5,000lb max. proof load.

*No.1093/S Loop Tops have a 7/8" loop diameter and are not compatible with some standard sized locking snap hooks. Use Steel or Aluminum auto-locking carabiners or rebar hooks.