

Commercial Roof Anchors • Risers

RLT Loop Top Riser Specifications

Use Rating	Riser Height	Part Name	Material			SAS Part No.	Top Fixture		Approx wt/lb
			Sch	O.D.	Type		No.	Type	
Rated For Window Washing 1 Person PPE Anchor HLL End and Intermediate Anchors	8 △	RLTW-8W	40	3.0"	▲RAW	1043-WR	1090	Q235	4.6
					▲HDG	1043-WG		Q235	
					304sst	1043-WS	1090-S	316sst	
					316sst	1043-WSX		316sst	
	12 △	RLTW-12W	40	3.0"	▲RAW	1044-WR	1090	Q235	6.9
					▲HDG	1044-WG		Q235	
					304sst	1044-WS	1090-S	316sst	
					316sst	1044-WSX		316sst	
	18 △	RLTW-18W	40	3.0"	▲RAW	1045-WR	1090	Q235	10.4
					▲HDG	1045-WG		Q235	
					304sst	1045-WS	1090-S	316sst	
					316sst	1045-WSX		316sst	
	24 △	RLTW-24W	80	3.0"	RAW	1046-WR	1090	Q235	17.0
					HDG	1046-WG		Q235	
					304sst	1046-WS	1090-S	316sst	
					316sst	1046-WSX		316sst	
	30 △	RLTW-30W	80	4.5"	RAW	1047-WR	1090	Q235	40
					HDG	1047-WG		Q235	
					304sst	1047-WS	1090-S	316sst	
					316sst	1047-WSX		316sst	
	36 △	RLTW-36W	80	4.5"	RAW	1048-WR	1090	Q235	48
					HDG	1048-WG		Q235	
					304sst	1048-WS	1090-S	316sst	
					316sst	1048-WSX		316sst	
30 △	RLTW-30W2 2.0" i.d. Loop Top	80	4.5"	RAW	1047-W2R	1093	Q345	42	
				HDG	1047-W2G		Q345		
				304sst	1047-W2S	1093-S	316sst		
				316sst	1047-W2SX		316sst		
36 △	RLTW-36W2 2.0" i.d. Loop Top	80	4.5"	RAW	1048-W2R	1093	Q345	50	
				HDG	1048-W2G		Q345		
				304sst	1048-W2S	1093-S	316sst		
				316sst	1048-W2SX		316sst		
1 Person PPE Anchor HLL End and Intermediate Anchors	30 △	RLT-30	80	3.0"	RAW	1047-R	1090	Q235	21.0
					HDG	1047-G		Q235	
					304sst	1047-S	1090-S	316sst	
					316sst	1047-SX		316sst	
	36 △	RLT-36	80	3.0"	RAW	1048-R	1090	Q235	24.0
					HDG	1048-G		Q235	
					304sst	1048-S	1090-S	316sst	
					316sst	1048-SX		316sst	



G = ASTM 123 Hot Dip Galvanized
 S = 304 Grade Stainless Steel
 SX = 316 Grade Stainless Steel
 Sch 40: A-36 = 0.0203/Q235 = 6mm(0.236)
 Sch 80: A-36 = 0.0276/Q235 = 8mm(0.314)

W = Rated For Window Washing.
 ▲ = Stock Part
 △ = On site proof load max. 2,500lb
 △ = Rated for HLL End anchors or single Person PPE
 R = Raw uncoated Steel

Note: Risers are supplied with sst vent hole socket head screw and PID label for installation after field welding.