

Commercial Roof Anchors • PT Risers

RPT Pass Through Riser Specifications

Material Type:

R = Raw uncoated Steel

G/HDG = ASTM 123 Hot Dip Galvanized

S = 304 Grade Stainless Steel

SX = 316 Grade Stainless Steel

▲ = Stock Part

Note: Unless specified by customer anchors will be supplied in 304 or 316 depending on material cost and availability.



Threaded Vent Hole

Use Rating	Riser Height	Part Name	Material			SAS Part No.	Top Fixture		Approx wt/lb
			Sch	O.D.	Type		No.	Type	
Use only For Horizontal LifeLine Intermediate Anchors	8	RPT-8	40	3.0"	▲ RAW	1043-PR	1091	Q235	4.6
					▲ HDG	1043-PG			
					304sst	1043-PS	1091-S	316sst	
					316sst	1043-PSX			
	12	RPT-12	40	3.0"	▲ RAW	1044-PR	1091	Q235	6.9
					▲ HDG	1044-PG			
					304sst	1044-PS	1091-S	316sst	
					316sst	1044-PSX			
	18	RPT-18	40	3.0"	▲ RAW	1045-PR	1091	Q235	10.4
					▲ HDG	1045-PG			
					304sst	1045-PS	1091-S	316sst	
					316sst	1045-PSX			
	24	RPT-24	40	3.0"	RAW	1046-PR	1091	Q235	17.0
					HDG	1046-PG			
					304sst	1046-PS	1091-S	316sst	
					316sst	1046-PSX			
	30	RPT-30	80	3.0"	RAW	1047-PR	1091	Q235	21.0
					HDG	1047-PG			
					304sst	1047-PS	1091-S	316sst	
					316sst	1047-PSX			
	36	RPT-36	80	3.0"	RAW	1048-PR	1091	Q235	24.0
					HDG	1048-PG			
					304sst	1048-PS	1091-S	316sst	
					316sst	1048-PSX			

Note: Risers are supplied with sst vent hole socket head screw and PID label for installation after field welding.