Anchors Apex Ridge Top Anchor



OVERVIEW

This anchor was developed specifically for production builders and roofing companies. It is installed directly over the roof decking and can be nailed down by the framing or roofing contractor. It eliminates the need to install a temporary anchor for fall protection thus saving time and money. The unique design allows the roofer to "course under" the tie-off tab with a full course of roofing material — no more cutting or notching the shingle to accommodate your safety anchors. The next course of roofing covers the anchor leaving the tie-off tab exposed. This is the only anchor on the market that allows the roofer to literally roof under/over without interrupting his install.

The APEX anchor is one of the lowest cost anchors available in the market. It is aesthetically pleasing and does not detract from the look of the roof. The APEX is powder coated in brown and blends in with most roofing materials but may also be painted to match the roofing color. Two APEX options are available: #2796 Ridge Mount anchor with two connector attachments and #2793 Hip Ridge anchor with one connector attachment.

Device: Fall Arrest Anchor Material: 11-gauge steel Coating: Zinc Coat & Powder Coat Install Hardware: 304 stainless steel nails

Min. Tensile: 5,000 pounds
Fall Indicator: Stem Deformation

Working Radius: Direction of Slope or Leading Edge

Specification Use: 1 person Fall Arrest **Max Weight:** 340 pounds with tools

Instruction Manual: English/Spanish/French **Engineering:** 3rd Party Certified

Compliance: OSHA 1926:502, 1910.66, ANSI Z359.1-07, A10.32-2012

