

Commercial Roof Anchors • RLT Risers

RLT Loop Top Field Weld Risers

RLT field welded risers are mfg. to the same specifications as our CRA models and have zero deformation with a 2,500lb load applied to the loop top at any angle. 3rd party certified and tested for compliance. Choose from pre-engineered designs or custom fabrication.

New ANSI Z359.18 Certification

Specifications

- 5,000lb Min. Tensile Strength
- Window Washing, PPE, HLL systems
- SST Threaded Vent Hole Plug
- Hot Dip Galvanized, (HDG), 304sst or 316sst
- SAS HLL system engineering
- 3rd party engineering by DH Glabe & Assoc.
Report available upon request
- Custom anchors available. Contact SAS Sales Team

No.1090 Cast Steel Loop Top

SST Threaded Vent Hole Plug



Compliance

ANSI Z359.18-17 Type A/T
Window Washing: ANSI/IWCA 1-14.1
OSHA 1926.502

Request Unit Pricing

Riser Height	Part Name	Part No.	Material Type	Pass-Thru Top		Riser Material		
				No.	Type	O.D/wt.	Sch	
8	RLT-8W	1043-WG	▲ HDG	1090	Q235	3.0"	40 0.203	
		1043-WS	304sst	1090-S	316sst	4.6lb		
12	RLT-12W	1044-WG	▲ HDG	1090	Q235	3.0"		
		1044-WS	304sst	1090-S	316sst	6.9lb		
18	RLT-18W	1045-WG	▲ HDG	1090	Q235	3.0"		
		1045-WS	304sst	1090-S	316sst	10.4lb		
24	RLT-24W	1046-WG	HDG	1090	Q235	3.0"		80 0.276
		1046-WS	304sst	1090-S	316sst	17lb		
30	RLT-30W	1047-WG	HDG	1090	Q235	3.0"		
		1047-WS	304sst	1090-S	316sst	22lb		
36	RLT-36W	1048-WG	HDG	1090	Q235	3.0"		
		1048-WS	304sst	1090-S	316sst	26lb		

Max. on site proof load 2,500lb

▲ Stock part

Note 1: Field welded risers cannot be foam filled prior to welding.
PID label supplied for installation after field welding.