

Commercial Roof Anchors • CRR Risers

CRR CAL-OSHA Compliant Field Weld Risers



ANSI Z359.18 Certification

CRR are the field welded version of our CRO anchor and comply to the same certification and compliance standards. Rated for window washing, single person PPE or HLL systems. Choose from pre-engineered or custom designs. CRR risers are mfg. in the USA

Specifications

- Min. Tensile Strength 5,000lb
- No.1093 Q345 and No.1093-S 316sst loop tops tensile strength rating of 20,000lb*
- Stainless Steel vent hole plug
- Hot Dip Galvanized (HDG), 304sst or 316sst
- 3rd party engineering by DH Glabe & Assoc.
Report available upon request
- Custom anchors available. Contact SAS Sales Team

Compliance

ANSI Z359.18-17 Type A/T*
 Window Washing: ANSI/IWCA 1-14.1
 CAL-OSHA Title 8
 OSHA 1926.502
 *Request CRO Intertek 2019 Lab Report



Request Unit Pricing

Riser Height	Part Name	Part No.	Material Type	Loop Top		Riser Material	
				No.	Type	O.D/wt.	Sch
8	CRR-8	1201-G	HDG	1093	Q345	4.5" 16lb	80 0.337
		1201-S	304sst	1093-S	316sst		
12	CRR-12	1202-G	HDG	1093	Q345	4.5" 19lb	
		1202-S	304sst	1093-S	316sst		
18	CRR-18	1203-G	HDG	1093	Q345	4.5" 30lb	
		1203-S	304sst	1093-S	316sst		
24	CRR-24	1204-G	HDG	1093	Q345	4.5" 38lb	
		1204-S	304sst	1093-S	316sst		
30	CRR-30	1205-G	HDG	1093	Q345	4.5" 81lb	XX 0.674
		1205-S	304sst	1093-S	316sst		
36	CRR-36	1206-G	HDG	1093	Q345	4.5" 93lb	
		1206-S	304sst	1093-S	316sst		

2,500lb max. on site proof load.

Note 1: Field welded risers cannot be foam filled prior to welding.
 PID label supplied for installation after field welding.