

Horizontal Lifeline Components • CRO-4

CRO-4 Horizontal Lifeline Anchor

CRO-4 and CRO 4-Way tops are the CAL-OSHA version of our CRA-4 HLL anchors. Bolt, field weld, or concrete embedment attachment to the supporting structure. Not specified for window washing anchors.

Specifications

- Tensile Strength 5,000lb
- Foam filled riser
- Hot Dip Galvanized (HDG), 304sst or 316sst
- 3rd party engineering by DH Glabe & Assoc.
Report available upon request
- Custom anchors available. Contact SAS Sales Team

Compliance

ANSI Z359.18-17 Type A*
OSHA 1926.502
**Request CRA Intertek 2020 Lab Report*

Ordering Information

- Order CRO-4 standard or custom model size.
- Order CRO 4-Way Top
Includes required fasteners

CRO 4-Way Top Fixture wt. 15.5lb

Part Name	Part No.	Material Type	Cast Loop Top
CRO 4-Way	▲1400-4WG	Hot Dip Galvanized	1093 Q345 Steel

No.1093 Cast Steel Loop Top

Component attachment
9/16" Bolt Holes

Height
Above
CRO-4
Riser
4-1/2"

CRO-4
Attachment
Bolt Hole

Overall
Height
8-1/2"

3 Place SST
Socket Screws

Bonded SST
Seal Washers

1/2"x7.0" 18-8sst
Attachment Bolt
w/Lock Nut

CRO-4 Standard Models

Riser Height	Part Name	Part No.	Material Type	Riser		Base Plate
				O.D /wt	Sch	
△ 8	CRO-4-8	1400-4G	HDG	4.5"	35lb	12"x12"x5/8" 4 or 8 Bolt Hole
		1400-4S	304sst			
△ 12	CRO-4-12	1401-4G	HDG	4.5"	49lb	12"x12"x3/4" 4 or 8 Bolt Hole
		1401-4S	304sst			
△ 18	CRO-4-18	1402-4G	HDG	4.5"	66lb	12"x12"x1.0" 4 or 8 Bolt Hole
		1402-4S	304sst			
△ 24	CRO-4-24	1403-4G	HDG	4.5"	79lb	12"x12"x1-1/8" 4 or 8 Bolt Hole
		1403-4S	304sst			
△ 30	CRO-4-30	1404-4G	HDG	4.5"	137lb	12"x12"x1-1/4" 4 or 8 Bolt Hole
		1404-4S	304sst			
△ 36	CRO-4-36	1405-4G	HDG	4.5"	158lb	12"x12"x1-3/8" 4 or 8 Bolt Hole
		1405-4S	304sst			

Do not proof load 4-Way Tops

▲ Stock part

△ Bolt attached, concrete embedment or field weld.

CRO-4 Anchor

