

# Horizontal Lifeline Components

## Jaw-Jaw Turnbuckles

Turnbuckles are specified for use with SAS HLL systems and are compatible with SAS end anchors and couplers. A primary component for adjusting the HLL cable tension. Supplied with 18-8sst attachment bolts/lock nuts and replaceable PID and inspection labels. All components shown here are stock parts ready to ship.



### No.1058 HDG Turnbuckle

- Hot Dip Galvanized.
- 2ea 5/8"x3.0" Loop Top Bolts
- 1ea 9/16"x3.0" 4 Way Bolt
- Working load 5,200lb
- Min. breaking strength 26,000lb
- Max. length adjustment 11-1/2"
- Frame: 3/4"x14.0
- Pkg/wt.6lb

### No.1058-S 316sst Turnbuckle

- 316 Stainless Steel
- 2ea 5/8"x3.0" Loop Top Bolts
- 1ea 9/16"x3.0" 4 Way Bolt
- Working load 5,200lb
- Min. breaking strength 15,600lb
- Max. length adjustment 5-1/2"
- Frame: 3/4"x8-1/2"
- Pkg/wt. 5lb"

## HLL Cable Components

**No.1056**  
Galvanized



**No.1056-S**  
Stainless Steel



### 3/8" Cable Clamps

3 clamps are required for field swaging one HLL eye thimble.  
Fits 3/8"x7x19 cable

**No.1057**  
Galvanized



**No.1057-S sst**  
Stainless Steel



### 3/8" Cable Thimble

Required for HLL cable terminations.

### 3/8"x7x19 Wire Rope

Use for HLL cable. Order by the ft.



Part No.	Type	Strength	Wt/ft
1055-X	Galvanized	14,000lb	2.43lb
1055-SX	316sst	12,500lb	



Note: SAS recommends to add 5% to the projects estimated cable length.

### Factory Swage Eye Thimble



Part No.	Material	Part Name
1052-G	Galvanized	Factory Swage
1052-S	SST Thimble	

Part No.	Type	Pkg/wt.
1pc No.1056	Galvanized	0.5lb
1pc No.1056-S	316sst	

Part No.	Type	Pkg/wt.
1pc No.1057	Galvanized	0.5lb
1pc No.1057-S	316sst/304sst	

### Connector O-Ring

Use for connecting PPE to HLL cable.



### Part No.50105M

- 3,600lb proof load
- 5,000lb tensile strength
- Stamped steel zinc plated