Standing Seam Anchor HLL Systems

Standing Seam Anchor HLL Components


No.1207 standing seam anchors provide a practical solution for permanent or temporary HLL's using low profile CRA-W and CRA-PT anchors and HLL rigging kits.

Permanent HLL

Install No.1207 anchor with No.1208 SSC or No.8511 RCT seam clamps using CRA-W5 end and CRA-PT5 pass-thru anchors with SAS HLL kits No.1050-G or No.1051-S.









Rigging	No. Persons
Fall Restraint	4
Fall Arrest	2



No.1207 w/No.1208 Seam Clamps No.1031-W Anchor

Note: The combined height of CRA No.1031, seam clamps and No.1207

w/lock nuts and washers.

base plate places the HLL rope approx. 8-3/4" above the metal panel surface.

No.1031-P Pass-Thru

Intermediate anchor

O-Rings -0032

No. Persons

"B" end

No.1028 Swivel-D

Factory or Field Swage

User Specifications

Rigging

Fall Restraint

No.1031-W Anchor

"B" end

No.1081-S Coupler

Temporary HLL

Combine No.1325 HLL Rope Kit with No.1207 standing seam anchor for a temporary HLL system up to 100ft in length.



- HLL Rope System No.1325 Max. Length 100ft -

51

Specify HLL length -