

HLL Rope Systems 30° Fixed Length

HLL Rope System

Another SAS exclusive. Fixed length 30° HLL ropes are mfg. with 5/8" d. Double-Braid kernmantle type rope and mechanically swaged at our factory in Monroe, WA. USA. Light weight HLL ropes are ideal for reducing surface damage to metal panel roofing but can be used on all types of surfaces. Combined with our low abrasion HLL rope accessories or bi-directional rope grab. Each system is custom built.

Specifications

- Min. Tensile Strength 5,000lb
- 5/8" d. Double-Braid rope
12,000lb(54kN) tensile strength
- Aluminum swage w/clear PVC cover
- Plastic eye thimble
- 3,600lb(16kN) gate strength snap hooks
- PID, Inspection and accessory labels
- Instruction manual

No. 1326 30° Fixed Length Ropes

Part No.	Rafter Length	Finished Δ Length	Approx Wt/lb
1326-10	10ft	11'-6"	3.5
1326-12	12ft	13'-6"	4.5
1326-14	14ft	16'-0"	5.5
1326-16	16ft	18'-4"	7.5
1326-18	18ft	20'-6"	8.5
1326-20	20ft	23'-0"	9.5

Δ Snap hook to snap hook ends.

User Specifications


Rigging	No. Persons
Fall Arrest	1
Fall Restraint	2

Snap Hook Compliance

ANSI Z359.12-0
HLL: ANSI Z359.1-07
OSHA 1926.502

Ordering Information.

Specify by part number a max of 2 accessories of the same or mixed types for each HLL length. Captive connectors are not removable.



Connector Sleeve No.1326-CS

The tube webbing design provides a cover for snap hooks and carabiners to prevent damage to metal panels. Hook/Loop closure secures the cover to the lifeline.

No.5014 3" o.d. Removable O-Ring



No.1326-RC Captive Rope Coupler



No.4015-VLL Value Rope Grab

