



Customer Information:		
Sold to:		
Street Address:		
City:	State:	Zip:
Phone:	Cell:	
Ship to:		
Street Address:		
City:	State:	Zip:

Purchaser Contact Information:	
Name:	
E-mail:	
Purchase Order No.	Date:
Quote By: Super Anchor Safety Sales Person:	
Name:	Date:
Ph:	e-mail:

Connector Specifications: ANSI Z359.12/CSA Z259.12 • 3,600lb gate strengths • Zinc plated finish

6042-X
Nylon
18,000lb

6043-X
Polyester
14,000lb

"A" end Mark Boxes **"B" end**

Concrete Sleeve Specify Length



No.6041-X

Loop Only

Loop Only



Lrg. Slotted Stamped D-ring No.5004



Sm. Slotted Forged D-ring No.5007



Flat Stamped D-ring No.5012



Forged 304sst D-ring No.5017-S

Aluminum Carabiner No.5006-Z



Steel Carabiner No.5001-Z



Note: No.5007 Small D-ring Fits thru No.5004 and No.5012

Note: Wear Pads

Wear pads included on No.6042-X nylon webbing. Wear pads not available on No.6043-X polyester webbing.



Ordering Instructions:

- 1) Complete a worksheet for each separate design. Specify number of units required.
- 2) Complete Customer, Purchasers and Shipping information and forward to SAS sales person by e-mail.
- 3) Upon receiving your quote, sign the "Authorized By", enter date, and resend to SAS sales person.

Purchaser to Specify Shipping

Free UPS ground in the continental US.

 Will Call
Monroe WA.

 UPS
Ground

Shipping Options

 Next Day

 2nd Day

 3rd Day

Ship to:

 HI

 AK

 Canada

Part No.	▲ Finished Length	Qty	Cost/ea	Total
6042-X Nylon	in"			
6043-X Polyester	in"			
6044-XA Assembly Fee				
6041-X Sleeve	in"			
5004 Lrg. Slot D-ring				
5007 Sm. Slot D-ring				
5012 Flat D-ring				
5017-S sst D-ring				
5006-Z ▲ Alum Carabiner				
5001-Z Steel Carabiner				
▲ Anodized Finish				
▲ 18" added to cut length for terminations			Subtotal wo/sales tax	
<input type="checkbox"/> Specify No. Units Required			Shipping charges	
			Total amount	

Customer: Sign and return to SAS after confirming unit price.

Authorized

By: _____ Date: _____