

CSA Personal Energy Absorbers

Standard Models

Snaphooks: Forged zinc plated
Carabiners: Aluminum auto-lock
D-Rings: Stamped zinc plated

Dielectric Connectors: 9kV min. dielectric resistance
Note: CSA E/A's mfg. with rope grabs are specified for use with vertical lifelines only. See section in our catalog.

User wt. Range: 135-310lb [60-140kg]

	No.6180-Z	No.6180-ZC	No.6181-Z	No.6182-Z	No.6183-Z	No.6183-ZC
	Snaphook	Snaphook	Snaphook	Snaphook	No.5006-Z Anodized Aluminum Carabiner	No.5000-ZY Captive Aluminum Carabiner
A-end						
	Shock Pack Approx. Length 18.0" [45.7cm]	Service Length 21.0" [53cm] wt. 23 oz [652.3g]	Service Length 24.0" [61cm] wt. 27 oz [765g]	Service Length 25.0" [63cm] wt. 36 oz [1,020g]	Service Length 24.0" [61cm] wt. 27 oz [765g]	Service Length 20.0" [51cm] wt. 13 oz [368.5g]
B-end	Loop End	No.5006-Z Anodized Aluminum Carabiner	Snaphook	No.5004 D-ring	Loop End	Loop End