

CSA Compliant Personal Energy Absorbers with Fall Arresters

For use in Canada, CSA requires vertical lifelines to be supplied with a synthetic rope fall arrester equipped with a panic grab function. The energy absorbing component must not exceed 30" in length and the fall arrester must be factory attached to the E/A. Shown here are CSA certified replacement Fall Arresters for use only on SAS mfg. Value-Z™ Lifelines No.4025-Z. Yoke mfg. fall arresters are of the highest quality and have proven to be the most reliable.

Features

User wt. Range: 135-310lb

Compliance: CSA Z259.2.5

Lifeline: Value™ 5/8" 3 Strand

Fall Arrester: Zinc plated No.4015-Z

w/Panic Grab Function. Yoke mfg.

Max. Deceleration: 39"

CSA specified counter weight not shown

Advisory

Replacement Fall Arresters w/factory attached E/A's are required to be used only on SAS Value-Z™ Lifelines No.4025-Z when used in Canada.

No.4025-SHC Value-Z™ Lifeline

Snaphook

Aluminum Swage

PID Labels

Clear PVC *Shrink Tube

No.6180-ZZ Energy Absorber

Vertical Lifeline E/A's are required by CSA to be factory attached to the fall arrester

Replacement Fall Arresters w/Factory Attached E/A's

No.6180-ZZ Snaphook

No.6183-ZZ No.5006-Z Aluminum Anodized Auto-lock Carabiner

No.6183-ZCC No.5000-ZY Aluminum Auto-lock Captive Carabiner

No.6190-ZUL Ultra-Lite™ Dee-Loop

Service Length 21.0" [53cm] wt.42 oz [1,190g]

Service Length 20.0" [51cm] wt.34 oz [963g]

Service Length Cinched 25.0" [63cm] wt.28 oz [793g]

No.4015-Z Fall Arrester

Aluminum Swage Stopper w/Clear PVC *Shrink Tube

13

*Shrink tube has an interior adhesive to prevent movement and is replaceable.

*Shrink Tube Termination