

ANSI Compliant Personal Energy Absorbers

Standard/Dielectric/Heavy Duty/6ft-12ft Models

Dielectric Connectors

ANSI and CSA certified 9kV min. dielectric resistance. Ideal for applications where electrical shock hazards are present. Use with SAS No.DE-6001 dielectric full body harness. Mfg. at SAS factory in Monroe, WA, USA.

6ft/12ft

No.6181-12 is specified for a 6ft free fall when attached overhead and 12ft free fall when attached at foot level.

No.6181-12X is available with optional connectors on the B-end. See E/A 6181-12X custom worksheet.

No.6181-12 Snaphook

A-end



User wt. Range: 130-310lb

No.6184

No.5006-Z
Anodized
Aluminum Carabiner

No.6184-C

No.5000-ZY
Captive Aluminum
Carabiner

No.6185

Loop End

No.6188

No.5017-Z
Dielectric Snaphook

User wt. 200-340lb

No.6186-HD

Snaphook



Service Length
23.0"
wt.
18 oz.

No.5004
D-ring



Loop End

Shock Pack
Approx.
18.0"
wt.
8 oz.



No.5018
Dielectric D-ring

Service Length
24.0"
wt.
28 oz.



No.5004
D-ring

Service Length
26.0"
wt.
33 oz.

6ft
Web
Lanyard



Service Length
72.0"
wt.
43 oz.

B-end



Snaphook