

ANSI Compliant Personal Energy Absorbers

Ultra-Lite™ Dee-Loop Series

Ultra-Lite the next generation in energy absorbers. Eliminating the "A" end connector reduces the absorber weight by nearly 50% and results in a more comfortable attachment. Recommended for use when the E/A removal is not required from the full body harness. Mfg. at SAS factory Monroe, WA, USA.

User wt. Range: 130-310lb

Simple as 1-2-3

No.6190
Ultra-Lite™
Dee-Loop

No.6192
Ultra-Lite™
Dee-Loop

No.6193
Ultra-Lite™
Dee-Loop

No.6194
Ultra-Lite™
Dee-Loop

1.
Feed Dee-Loop
thru harness
D-ring

2.
Feed shock
pack thru
Dee-Loop



Shock
Pack
Length
Approx.
18.0"

Service
Length
Cinched
27.0"
wt.
13 oz.

Service
Length
Cinched
26.0"
wt.
14 oz.

Weight Comparison
No.6190 Ultra-Lite™ wt. 23 oz.
No.6181 Standard E/A wt. 38 oz.

SAS No.6008
Full Body Harness
w/Hi-Viz™ Webbing

3.
Cinch Knot



E/A
No.6192
Service
Length
Approx.
26.0"

No.5000-ZY
Captive
Aluminum
Carabiner

No.5006-Z
Anodized
Aluminum
Carabiner

No.5004
D-ring

No.5018
9kV min. Dielectric
Resistance D-ring