

ANSI Compliant Personal Energy Absorbers with Fall Arresters

Fall Arresters w/Panic Grab Function

Fall arrester rope grabs are a critical component for adjusting a workers position on a synthetic rope lifeline. The Yoke model fall arresters are better designed than other fall arresters made by other manufacturers and are easily removed from the lifeline. The panic grab feature reduces the possibility of a worker accidentally disengaging the locking function when subjected to a free fall.

Fall Arrester Specifications

- **Compliance:** ANSI Z359.15
- Max. deceleration 39"
- Zinc plated or stainless steel
- Single direction locking function
- Serial numbered
- Panic grab function
- Removable
- Compatible with 5/8" synthetic lifelines.

Energy Absorber

- Mfg. at SAS factory Monroe, WA, USA.
- **Compliance:** ANSI Z359.13-13



User wt. Range: 130-310lb

No.6191-C
Ultra-Lite™
Dee-Loop



No.4015-C
Stainless Steel
Fall Arrester

No.6191-Z
Ultra-Lite™
Dee-Loop



No.4015-Z
Zinc Plated
Fall Arrester

No.6195-C
Snaphook



No.4015-C
Stainless Steel
Fall Arrester

No.6195-Z
Snaphook



No.4015-Z
Zinc Plated
Fall Arrester

Shown with
No.4083
Maxima™
Lifeline

Shock
Pack
Length
Approx.
18.0"

Service
Length
Cinched
25.0"
wt. 28 oz.

Service
Length
21.0"
wt.
42 oz.