# Harness Accessories

Max.

0.135

[3.3mm]

### Snap-Lock Webbing Keepers

Damaged or missing plastic webbing keepers are easily replaced with 2pc clip on snap-lock keepers. Order original parts for maintenance or repair. Specified for use with all SAS mfg. harnesses or those mfg. by others.

> Max. Width 1-3/4" [44mm]

### No.5020-WK

10ea 2pc Snap-Lock Plastic Webbing Keepers

### **Specifications**

- Fits 1-3/4"[44mm] wide webbing
- Max. webbing thickness 0.135
- Clip on attachment
- Includes instructions



Elastic Webbing Keepers


Nothing is more obnoxious than excess webbing left over from length adjustments. Control loose webbing ends and prevent snagging hazards with our OEM elastic webbing keepers. Standard issue for SAS mfg. harnesses and are easily replaced or retro-fitted to equipment mfg. by others.

### Nn.6410-3**Specifications**

• 3pc package

Triangle Connector

- Fits 1-3/4" [44mm] harness webbing
- 3" length elastic
- Includes instructions







### Lanuard Parks

ANSI Z359.11 and CSA Z359.10. require harnesses to be equipped with lanyard parks that have a max. release force of 150lb. Our hook/loop wrap design is easily retro-fitted to SAS Deluxe model and standard model harnesses or harnesses mfg. by others.





1-3/4" Webbing

# **Specifications**

- Fits all Deluxe™ models with padded frames
- Fits 1-3/4" wide harness webbing

30

## Hook/Loop

(Generic name for Velcro®) We use a double sided material especially designed for this type of application.

Supports Large Rebarhooks



Deluxe Padded Frame