

Personal™ Energy Absorbers

Personal Energy Absorbers (E/A's), are a critical component in meeting fall protection standards and are required when workers are exposed to free fall hazards. We mfg. a complete line of E/A's at our Monroe, WA USA factory.



Features

- 100% polyester webbing
- ANSI/CSA certified tear webbing.
- 3,600lb(16kN) gate strength connectors
- Loop end wear pads
- Clear PVC shock pack cover
- Date of mfg. serial numbered w/annual inspection label
- Fall indicator
- English/Spanish/French labels and instruction manuals
- Supplied in retail package

Compliance

ANSI Z359.13-13
CSA Z259.11-17

Performance Specifications

User wt's: ANSI=130-310lb (140kg)
CSA=135-310lb (140kg)
Max. Arrest Force: 1,800lb (8kN)
Avg. Arrest Force: 900lb (4kN)
Max. Deployment: 48" (1.2m)
Max. Free Fall: 6ft (1.8m)

Ultra-Lite™ Dee-Loop E/A's

The lightest E/A we mfg. attaches directly to the harness dorsal D-ring via a chinch knot. The elimination of a class 1 connector at the A-end results in a significant reduction in the components service weight and provides a higher level of comfort. Consult SAS Absorber catalog for additional model types. Mfg. exclusively at our Monroe, WA USA factory.

Harness D-ring Attachment

Feed Dee-Loop thru D-ring Feed shock pack thru Dee-Loop



No.3004

No.6182

No.6184
w/No.5006-Z
Anodized Alum
Carabiner

No.6193

Ultra-Lite™
Dee-Loop

"A"
end

Service Length
Measured from
connector
end to
connector
end

Service Length
Cinched
26.0"

No.4015-M
Integral
Adjuster
Rope Grab

"B"
end

Ordering Information

Part No.	Length	wt.	A-end	B-end	wt.
3004	23.0"	38oz	Snaphook	4015-M	38oz
6182	24.0"	27oz		No.5004 D-ring	27oz
6184	23.0"	18oz	Carabiner	No.5004 D-ring	18oz
6193	26.0"	14oz	Dee-Loop		14oz

Retail Package



17
Consult SAS USA/CSA Energy Absorber catalogs for additional information
www.superanchor.com 1-855-301-4575