

MAX-V™ Fall Protection Kit

Features

- No.6069 Value™ Universal size 5pt full body harness w/Hi-Viz™ polyester webbing w/serial number and inspection label
- 3.0" length elastic webbing keepers
- No.6181 energy absorber with "A" and "B" end 3,600lb gate strength snaphooks
- No.4015-M integral adjuster rope grab
- Maxima™ co-polymer lifeline with aluminum swaged termination and clear PVC shrink tube cover
- No.3013-D Hinge-2™ adjustable slope reusable anchor with dual fastener holes for nails or WS screws
- No.2012-A 36pc zinc plated duplex nails
- English/Spanish 20pg instruction manual

ANSI Compliance

Harness: Z359.11-14

Energy Absorber: Z359.13-13

Lifeline: Z359.15-14

Hinge2: Z359.18-17 Type A

Max-V™ No.3200-B is our version of an industry standard complete fall protection kit supplied in an attractive retail 5 gal bucket. The No.6181 energy absorber provides a quick disconnect from the integral adjuster (rope grab). Assembled at our SAS factory in Monroe, WA USA

No.6069 Value™ 5 Point Harness

- Hi-Viz™ Webbing
- Pass-Thru Buckles
- Lanyard Parks
- 3.0" Elastic Webbing Keepers
- Fall Indicators
- Dorsal D-ring
- Aluminum Swaging

No.6181 Energy Absorber

- Service Length 27.0"

No.4015-M Integral Adjuster Rope Grab

No.3013-D Hinge-2™ Adjustable Reusable Anchor

No.2012-A 36pc Zinc Plated Duplex Nails

Maxima™ 3 Strand Lifeline

Max-V Bucket 5 gallon

English Spanish 20 page manual

Side Panel
English
Spanish
French
Child Warning!

2018 SUPER ANCHOR SAFETY FALL PROTECTION MANUAL

Ordering Information

Part No.	Lifeline	Harness	wt/lb
3200-B25	25ft	Universal	14
3200-B50	50ft		16

Full Pallet=48 units

2 Size Fastener Holes for Nails or WS Screws