Lifelines

Synthetic fiber vertical lifelines are a key component of a personal fall protection system and are used with a rope grab for position adjustment. SAS offers several rope types and custom mfg.

All SAS Lifelines

- Assembled and swaged at SAS factory in Monroe, WA USA
- PID, inspection label and serial no.
- Aluminum swage w/clear PVC cover
- 3,600lb gate strength snaphook
- English/Spanish instruction manual
- Compatible with all SAS rope grabs Compliance

ANSI Z359.1-07/OSHA 1926.502

SAS Factory Swage

• User wt.: 340lb

PID Label

Large Diam. Plastic

Eve Thimble

No.4034 Deluxe™ Lifeline is a 12 strand commercial grade rope that is mfg. in the USA from the highest quality materials. Extremely durable.

Features

- 5/8"(16mm) d. polyolefin
- 11,600lb tensile strength
- UV resistant coating
- Red color for high visibility
- No.4015 SuperGrab™
- Supplied in a retail box

Ordering Information

| Part No. | Length | wt/lb |
|-----------|--------|-------|
| 4034-30SG | 30ft | 4 |
| 4034-50SG | 50ft | 5 |

English/Spanish 20 Page Manual





No.4015

SuperGrab™

No.4034-56



PVC Adhesive Shrink Tube



Custom length and connector types available. Contact SAS sales team.

No.4020 Value™ Lifeline

Aluminum

Swage

is an industry standard low cost high quality 3 strand lifeline

Features

- 5/8"(16mm) d. polyolefin
- 9,700lb tensile strength
- Supplied in a retail box



Inspection

Label

Clear PVC

Cover







| oruenny inionnai | | |
|------------------|--------|-------|
| Part No. | Length | wt/lb |
| 4020-25 | 25ft | 4 |
| 4020-30 | 30ft | 4 |
| 4020-50 | 50ft | 5 |
| 4020-75 | 75ft | 7 |
| 4020-100 | 100ft | 10 |

No.4083 Maxima™ Lifeline

is our most economical 3 strand lifeline.

Features

- 5/8"(16mm) d. co-polymer
- 10,582lb tensile strength
- Supplied in a retail box



Retail Box

Ordering Information

| or acrining | acring information | |
|-------------|--------------------|-------|
| Part No. | Length | wt/lb |
| 4083-25 | 25ft | 4 |
| 4083-30 | 30ft | 4 |
| 4083-50 | 50ft | 5 |
| 4083-100 | 100ft | 9 |



| Part No. | Length | wt/lb |
|----------|--------|-------|
| 4020-25 | 25ft | 4 |
| 4020-30 | 30ft | 4 |
| 4020-50 | 50ft | 5 |
| 4020-75 | 75ft | 7 |
| 4020-100 | 100ft | 10 |