

Fasteners/Carabiners

SAS Fasteners

All fasteners supplied with anchors and sold as replacements are tested and certified to perform as specified in our instruction manuals. SAS does not recommend using generic non-certified fasteners even when they may appear to be similar types.

WS Screws

- Use for all SAS anchor models specifying WS screws
- Includes 3/8" hex driver
- Anti-corrosion coating

Ordering Information

Part No.	Length	Pcs	Pkg
2084-1.5	1.5"	25	Box Inside Retail Pkg.
2084-2.0	2.0"		
2084-2.5	2.5"		
2084-3.0	3.0"		
2084-3.5	3.5"	10	

WS Screw



Hex Driver



Retail Package



Screws/Nails

Ordering Information

Part No.	Type	Length	Pcs/Pkg
2012-A	16d Duplex	3.0"	36 Retail
2013	12d SST Nail		
2045-3.0	SST Bugle Head Screw	3.0"	
2045-3.5		3.5"	
2022	CRA Hex Screw	2.5"	40 Retail

Zinc Coated Duplex



SST Spiral Shank



SST Bugle Head



Hex Head Screw w/Coating



Retail Package



Fall Protection Carabiners

No.5001-Z

- Twist Lock zinc plated steel
- 3,600lb gate strength
- 41kN tensile strength
- ANSI-Z359.12-09
- CSA-Z259.12-11
- English Manual



Retail Package



Ordering Information

Part No.	Pcs	Pkg	Wt.
5001-Z	1	Retail	8.9oz
5006-Z			5.2oz

No.5006-Z

- Twist Lock light wt. anodized aluminum
- 3,600lb gate strength
- 24kN tensile strength
- ANSI-Z359.12-09
- CSA-Z259.12-11
- English Manual



Retail Package



Description

SAS standard issue carabiners specified for use with energy absorbers, lifelines and lanyards. We use only the highest quality ANSI/CSA certified manufacturers for your quality assurance.