

RLT Loop Top Field Weld Risers

3.0"od. RLT Field Weld Risers

Specified for single person PPE anchor point, window washing tie-off and horizontal lifeline lengths up to 240ft. 3rd party certified to comply with current ANSI, CSA and OSHA fall protection standards.

Specifications

- Min.tensile strength 5,000lb
- No.1090 Q235 steel and 1090-S 316sst loop tops tensile strength rating of 10,000lb*
- Hot dip galvanized (HDG), 304sst or 316sst
- 3rd party engineering by DH Glabe & Assoc.
Report available on request
- Contact SAS sales team for custom mfg. and lead times

Compliance

ANSI Z359.18-17 Type A/T*

CSA Z259.15:22 Type A/T*

Window Washing: ANSI/IWCA I-14.1

OSHA 1926.502

*Request Intertek CRA Lab Report

No.1090 Cast Steel Loop Top 1-3/8" id.

PID Label w/Serial No. SST Threaded Vent Hole Plug



Field Weld to Structural Steel



Request Unit Pricing

Riser Height	Part Name	Material		Loop Top		Anchor wt/lb	Riser ▲Sch
		Part No.	Type	No.	Type		
8	RLT-8W	1043-WG	▲ HDG	1090	Q235	6	40 0.203 3.0"od.
		1043-WS	■ 304sst	1090-S	316sst		
12	RLT-12W	1044-WG	▲ HDG	1090	Q235	8	
		1044-WS	■ 304sst	1090-S	316sst		
18	RLT-18W	1045-WG	▲ HDG	1090	Q235	12	
		1045-WS	■ 304sst	1090-S	316sst		
24	RLT-24W	1046-WG	■ HDG	1090	Q235	16	80 0.276 3.0"od.
		1046-WS	■ 304sst	1090-S	316sst		
30	RLT-30W	1047-WG	■ HDG	1090	Q235	20	
		1047-WS	■ 304sst	1090-S	316sst		
36	RLT-36W	1048-WG	■ HDG	1090	Q235	26	
		1048-WS	■ 304sst	1090-S	316sst		

■ Standard Design Custom mfg. ▲ Nominal Dimension. ▲ Stock Part.

Note 1: Max. proof load 2,500lb.

Note 2: If required, foam filling to be provided by contractor after welding.

Note 3: PID label supplied loose for application after welding.

Sloped HDG/304sst Risers

RST-A RST-B



Contact SAS sales team for custom mfg. and lead times Part No. reference **1043-X**