

RPT Pass-Thru Field Weld Risers

3.0"od. RPT Field Weld Risers

Intermediate anchors for CRA HLL systems up to 240ft. w/max. 30ft spacing between anchors. Pass-Thru tops are designed for use with connector ring No.5010-SM providing travel between intermediate anchors along the entire length of the HLL cable without disconnecting.

Specifications

- Horizontal lifeline intermediate anchor
- Min. tensile strength 5,000lb
- No.1091 Q235 steel or 1091-S 316sst pass-thru tops
- Hot dip galvanized (HDG), 304sst or 316sst
- HLL 3rd party engineering by DH Glabe & Assoc.
Report available on request
- Contact SAS sales team for custom mfg. and lead times

Compliance

ANSI Z359.1-07
OSHA 1926.502

No.1091 Cast Steel Pass-Thru Top

PID Label w/Serial No.
SST Threaded Vent Hole Plug



Field Weld to Structural Steel



Request Unit Pricing

Riser Height	Part Name	Material		Pass-Thru Top		Anchor wt/lb	Riser ▲Sch	
		Part No.	Type	No.	Type			
8	RPT-8	1043-PG	■ HDG	1091	Q235	6	40 0.203 3.0"od.	
		1043-PS	■ 304sst	1091-S	316sst			
12	RPT-12	1044-PG	■ HDG	1091	Q235	8		
		1044-PS	■ 304sst	1091-S	316sst			
18	RPT-18	1045-PG	■ HDG	1091	Q235	12		
		1045-PS	■ 304sst	1091-S	316sst			
24	RPT-24	1046-PG	■ HDG	1091	Q235	16		
		1046-PS	■ 304sst	1091-S	316sst			
30	RPT-30	1047-PG	■ HDG	1091	Q235	20		80 0.276 3.0"od.
		1047-PS	■ 304sst	1091-S	316sst			
36	RPT-36	1048-PG	■ HDG	1091	Q235	26		
		1048-PS	■ 304sst	1091-S	316sst			

- Standard Design Custom mfg. ▲ Nominal Dimension.
- Note 1: Do not proof load pass-thru tops.
- Note 2: If required, foam filling to be provided by contractor after welding.
- Note 3: PID label supplied loose for application after welding.

Sloped HDG/304sst Risers RSP-AP RSP-BP



Contact SAS sales team for custom mfg. and lead times
Part No. reference **1043-PX**