

# Horizontal Lifeline Rope Kit

Temporary HLL rope system is compatible with SAS mfg. anchors specified for HLL use.

## Specifications

- Min. tensile strength 5,000lb
- 15,000lb tensile strength 3/4" double braid kernmantle rope
- Ratchet type rope tensioner w/factory attached energy absorber
- Tensioner tool w/shock cord tether
- 3,600lb gate strength twist lock carabiners
- 4ea No.5014 3" od. O-Rings
- 2ea 6ft double D-ring heavy duty tie-off straps

## Compliance

ANSI Z359.1-07/OSHA 1925.502

Carabiners: ANSI Z359.12

## User Specifications

No. Persons	Rigging
2	Fall Arrest
4	Fall Restraint

Note: Workers required to wear a personal energy absorber specified for their wt.

## Rope Request Unit Pricing

Part No.	Length/ft	wt/lb
▲ 1325-60	60	28
▲ 1325-100	100	33

▲ Stock Part.

## Accessories Request Unit Pricing

Part No.	Description	wt/lb
▲ 1325-T	Rope Tensioner	3
▲ 4015-VLL	HLL Rope Grab	1
▲ 5014	3" od. O-Ring	1
▲ 6420U	Large Cargo Bag	3

▲ Stock Part.

## No.1325 Kit

6ft Double D-ring Tie-Off Straps



## No.6420U


Large All-Pakka™ Cargo Bag



## Accessory Components

No.4015-VLL HLL Rope Grab

Locks Onto HLL in Both Directions



## Compatible End Anchors

Consult anchor type instruction manual for installation requirements.

No.3013-D  
Hinge-2™




No.1062  
Evac™



No.1037  
D-Plate



CRA  
w/Loop Tops



No.2100  
Flex™



No.1028-DP6  
Swivel-D Plate



No.1207  
Standing Seam

