

CRR-PT Field Weld Risers

4.5"od. CRR-PT Field Weld Risers

Intermediate anchors designed for CRO HLL systems up to 240ft. w/max. 30ft spacing between anchors. Pass-Thru tops are designed for use with connector ring No.5010-SM providing travel between intermediate anchors along the entire length of the HLL cable without disconnecting.

Specifications

- Horizontal lifeline intermediate anchor
- Min. tensile strength 5,000lb
- No.1091 Q235 steel or 1091-S 316sst pass-thru tops
- Hot dip galvanized (HDG), 304sst or 316sst
- HLL 3rd party engineering by DH Glabe & Assoc.
Report available on request
- Contact SAS sales team for custom mfg. and lead times

Compliance

ANSI Z359.1-07
OSHA 1926.502



Request Unit Pricing

Riser Height	Part Name	Part No.	Material Type	Pass-Thru Top		Anchor wt/lb	Riser ▲ Sch
				No.	Type		
8	CRR-PT8	1201-PG	■ HDG	1091	Q235	19	80 0.337 4.5"od.
		1201-PS	■ 304sst	1091-S	316sst		
12	CRR-PT12	1202-PG	■ HDG	1091	Q235	21	
		1202-PS	■ 304sst	1091-S	316sst		
18	CRR-PT18	1203-PG	■ HDG	1091	Q235	30	
		1203-PS	■ 304sst	1091-S	316sst		
24	CRR-PT24	1204-PG	■ HDG	1091	Q235	37	
		1204-PS	■ 304sst	1091-S	316sst		
30	CRR-PT30	1205-PG	■ HDG	1091	Q235	46	
		1205-PS	■ 304sst	1091-S	316sst		
36	CRR-PT36	1206-PG	■ HDG	1091	Q235	55	
		1206-PS	■ 304sst	1091-S	316sst		

■ Standard Design Custom mfg. ▲ Nominal Dimension.

Note 1: Do not proof load pass-thru tops.

Note 2: If required, foam filling to be provided by contractor after welding.

Note 3: PID label supplied loose for application after welding.