

CRR-4 HLL 4-Way Field Weld Risers

4.5"od. CRR-4 HLL Field Weld Risers

Specified for HLL end and intermediate anchors field welded to a supporting structure.

Specifications

- Min. tensile strength 5,000lb
- Compatible w/SAS HLL accessories
- Hot dip galvanized (HDG), 304sst or 316sst
- 3rd Party engineering by DH Glabe & Assoc.
Report available on request
- Contact SAS sales team for custom mfg. and lead times

Compliance:

ANSI Z359.18-17 Type A/T
CSA Z259.15:22 Type A/T
OSHA 1926.502

Ordering Information:

- Order CRR-4 Model Size
- Order CRO 4-Way Top

9/16" d. Accessory Attachment Bolt Holes

CRR-4 Attachment Bolt Hole

No.1093 Cast Steel Loop Top 2" id.

4-Way Top
9-3/4" diam.

4-1/2"

Overall Height
8-1/2"

PID Label w/Serial No.

3 Place SST Socket Screws



CRO 4-Way Top


Part Name	Part No.	Type	Loop Top	wt/lb
▲ CRO 4-Way	1400-4WG	HDG	No.1093 Q345 steel	16

▲ Stock Part includes attachment bolt pkg. and socket screws.
Not available in stainless steel.

CRR-4 Field Weld Riser

4-Way Top Attachment Bolt Hole

12" Min. Riser Height Required For Flashing



Bolt Pkg.

1/2" x 7" 18-8sst
Attachment Bolt w/Lock Nut

Bonded SST Seal Washers



Request Unit Pricing

Riser Height	Part Name	Part No.	Material Type	4-Way □ Top	Anchor wt/lb	Riser ▲ Sch
12	CRR-4-12	1202-4G	■ HDG	1400-4WG	19	80 0.337 4.5" od.
		1202-4S	■ 304sst			
18	CRR-4-18	1203-4G	■ HDG		28	
		1203-4S	■ 304sst			
24	CRR-4-24	1204-4G	■ HDG		35	
		1204-4S	■ 304sst			
30	CRR-4-30	1205-4G	■ HDG		44	
		1205-4S	■ 304sst			
36	CRR-4-36	1206-4G	■ HDG		53	
		1206-4S	■ 304sst			

■ Standard Design Custom mfg. ▲ Nominal Dimension.

□ Order 4-Way top separately.

Note 1: Max. proof load 2,500lb.

Note 2: If required, foam filling to be provided by contractor after welding.