

8001-CFS Field Swage System

2 Level Pelican Case Equipment Storage

Level 1



Level 2



8001-CFS Equipment List

Part No.	No. pcs.	Part Name
8003.1	1	Milwaukee M-18 Crimper
8003.1CD	2	Crimper Dies
8003.1BT	2	M-18 Batteries
8001.1BC	1	M-18 Battery Charger
8003.2	1	Husky REC-S724H Cable Cutter
8003.2BT	2	Husky Batteries
8003.2BC	1	Husky Battery Charger w/12v converter + 120v cord
8003.3	1	Leister Hot-Jet S Heat Gun
8003.4	1	Lugg-All No.500-A Cable Puller w/threaded steel link
8003.4CG	1	RG14 3/8" Cable Grab
8003.4TL	1	3/16"x16ft Wire Rope Tag Line
8003.5	1	Sleeve Press w/Handle
8003.6	1	Pelican No.2875 Cargo Case w/2 Equipment Shelves
8003.6CL	2	Combination Locks
Weight	67.5lb	

8001-CFS Cable Swage HLL "A" End

Note: All end, intermediate and 4-Way anchors are installed with the HLL cable "B" end swage completed and attached to the "B" end anchor.

- Attach turnbuckle to "A" end anchor 3/4 open and all rigging accessories
- Connect tag line to CRA-PT top loop and cable puller hook
- Feed HLL cable thru 2 sleeves and PVC shrink tube
- Attach cable grab and puller
- Adjust cable puller webbing to remove slack from tag line
- Tighten cable puller until all HLL cable slack is removed
- Crimp sleeve #1 with M-18 press
- Remove cable grab, puller and tag line
- Perform sleeve press operation

