4.5" od. Sloped Anchors

The most common variations of standard SAS designs are shown here. Project specific designs are also available. Contact SAS sales team for custom mfg. and lead times.

Top Fixture Orientation No.1091/1091-S Pass-Thru Tops

Mounted onto 4.5" od. risers

HLL Direction -Pass-Thru Top Pass-Thru Top "BP" "AP" Parallel with Ridge Perpendicular to Ridge

No.1400-PX **CROS-AP**







CRRS-BP 60

No.1201-PX



No.1401-4X CROS-4





ŧ

VLL

Direction

No.1201-PX **CRRS-AP**



No.1202-4X CRRS-4





Anchors with Base Plates

Custom Specifications

• Material type and finish

• Base plate dimensions

• Bolt hole sizes and locations • Top fixture type and orientation • Degree of slope and angle • 3rd party engineering available

Pass-Thru Anchors • Intermediate HLL only

4-Way Anchors

• Riser height

• HLL ends • HLL intermediate • HLL 45°/90° intersections

Part	Part Name	Top Fixture		Riser
No.		Orientation	Туре	Slope
1400-PX	CROS-AP	"A"	Pass- Thru	Specify Degree of Angle or Pitch
	CROS-BP	"В"		

Field Weld Risers

Part No.	Part Name	Top Fixture		Riser
		Orientation	Туре	Slope
1201-PX	CRRS-AP	"A"	Pass- Thru	Specify Degree of Angle or Pitch
	CRRS-BP	"B"		

4-Way Anchors

Part No.	Part Name	Top Fixture 4-Way	Riser Slope
1401-4X	CROS-4	1400-4WG	Specify Degree
1202-4X	CRRS-4	1400-4₩0	of Angle or Pitch

Order 4-Way top separately.

93