

Super Anchor Safety 2024 Quick Reference

Swivel-D Anchor

One of our most versatile anchors requires a 300' minimum and 180° fix. Both attach, fasten and combine attachment to permanent or temporary installation.

No. 1028 Swivel-D*

Attachment Bolt
Cap Washer
3/16" Dia. Washer
Forged Clamping
Reducer Bolt
Swivel Bushing
Lock Nut
100' Plug
300' Retention
300' Inspection Labels

Swivel-D Specifications

- Min. tensile strength 5,000lb
- Forged D-ring
- 4-point steel design
- 5/8" attachment bolt
- S&S factory install report available on request

User Specifications

- Single person PPE
- HLL and anchors
- Window washing
- Compliance
- ANSI Z59.1-2017 Type A-1
- Window Washing (ANSI/SSA 314.1)

No. 1028 Swivel-D* Package Contents

- 1 No. 1028 Swivel-D anchor
- 5/8" x 1.14" set bolt

No. 1028-09K Package Contents

- 1 No. 1028 Swivel-D anchor
- 5/8" x 1.14" 100' base plate
- 5/8" x 1.14" threaded stud w/lock nut

No. 1028-09K Package Contents

- 1 No. 1028 Swivel-D anchor
- 5/8" x 1.14" 100' base plate
- 5/8" x 1.14" threaded stud w/lock nut

No. 1028-09K Package Contents

- 1 No. 1028 Swivel-D anchor
- 5/8" x 1.14" 100' base plate
- 5/8" x 1.14" threaded stud w/lock nut

Compatible Attachments

- Structural Steel
- No. 1028 Swivel-D
- Threaded Top Anchor

Request Unit Pricing

Part No.	Part Name	Description	Unit
A 1028	Swivel-D	Anchor only	1.00
A 1028-09K	Swivel-D	Anchor w/100' base plate	1.50
A 1028-09K	Base Plate	5/8" x 1.14" threaded stud	1.50
A 1028-09K	Base Plate	5/8" x 1.14" threaded stud w/lock nut	1.50
A 1028-09K	Base Plate	5/8" x 1.14" threaded stud w/lock nut	1.50

▲ Stock Part. Includes 1 Min. proof load @ 2,500lb.
Note 2: Base plates may be required for installation.

61

Swivel-D Metal Panel Anchor

Designed for installation with No. 1028 Swivel-D onto 2x4 wood purlins and metal Z-purlins used for pole buildings and steel framed commercial buildings. Use with flat and h-profile metal panel roofing.

Installation Over 2x4 Purlin

Swivel-D Attachment Bolt
No. 1028 Swivel-D
No. 1028-8P1 Base Plate

Attachment Bolt
2x4 Wood Purlin
No. 1028-8P2 Base Plate
3/8" x 1.31" x 2 1/2" x 1/4"

Installation Over Sheetpiling

Swivel-D Attachment Bolt
No. 1028 Swivel-D
No. 1028-8P1 Base Plate

Standing Seam Metal Panel
No. 1028-8P2 Base Plate
3/8" x 1.31" x 2 1/2" x 1/4"

Swivel-D Metal Panel Anchor Specifications

- Min. tensile strength 5,000lb
- Hot dip galvanized
- Full threaded retention
- Single person PPE
- Compliance
- ANSI Z59.1-2017
- OSHA 1926.502

No. 1028-8P1 Dimensions

1.31" x 2.5" x 1/4"

Has Screw Plug
3/8" Threaded Bolt Hole
3/8" Threaded Bolt Hole

No. 1028-8P2 Kit Contents

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P1 base plate
- 1 No. 1028-8P2 base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

No. 1028-8P1 Kit Contents

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P1 base plate
- 1 No. 1028-8P2 base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

No. 1028 Swivel-D Kit Contents

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P1 base plate
- 1 No. 1028-8P2 base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

Request Unit Pricing

Part No.	Part Name	Description	Unit
A 1028	Swivel-D	Anchor only	1.00
A 1028-8P1	Base Plate	5/8" x 1.14" threaded stud	1.50
A 1028-8P2	Base Plate	5/8" x 1.14" threaded stud w/lock nut	1.50
A 1028-8P1	Base Plate	5/8" x 1.14" threaded stud w/lock nut	1.50
A 1028-8P2	Base Plate	5/8" x 1.14" threaded stud w/lock nut	1.50

▲ Stock Part. Includes 1 Min. proof load @ 2,500lb.
Note 2: Base plates may be required for installation.

62

Swivel-D Z-Purlin Anchor

Designed for installation of No. 1028 Swivel-D over metal roofing panels onto metal Z-purlins.

Specified Use

- Single person anchor point
- Not used for HLL systems

No. 1028 Swivel-D

5/8" x 1.14" Attachment Bolt
No. 1028 Swivel-D
No. 1028-8P1 Base Plate

Z-Purlin
Top Flange
Flat Washer
3/8" x 1/2" Attachment Bolt

No. 1028-8P2K Z-Purlin Kit

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P2K base plate
- 1 No. 1028-8P2K base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

No. 1028-8P2K Kit

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P2K base plate
- 1 No. 1028-8P2K base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

Request Unit Pricing

Part No.	Description	Unit
A 1028	Swivel-D	1.00
A 1028-8P2K	Z-Purlin Kit	1.50
A 1028-8P2K	Z-Purlin Kit	1.50
A 1028-8P2K	Z-Purlin Kit	1.50

Universal Bolt Kit for 1028-8P2K Kit

- No. 1028-8P2K
- 1 No. 1028-8P2K base plate
- 1 No. 1028-8P2K base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

63

Wood Purlin Anchor

Designed for installation onto double 2x4 wood purlins commonly used in pole buildings. Use for temporary or permanent full penetration.

Specification

- Min. tensile strength 5,000lb
- 3/16" hot dip galvanized
- Details w/ 90° corners
- Single person PPE and/or HLL system
- Permanent/temporary use for full area/full retention

Compliance

- ANSI Z59.1-2017
- OSHA 1926.502

No. 1302-2XM*

Depth 3/16"
Length 11-1/2"
Width 3/16"
3/16" Thickness

Installation

Anchor attaches where wood purlins overlap.
Anchor to double 2x4 purlins with 8 1/2" x 1 1/2" WS wood screws.

Temporary

No. 1028 Swivel-D
No. 1028-8P1 Base Plate
No. 1028-8P2 Base Plate

Permanent

No. 1028 Swivel-D
No. 1028-8P1 Base Plate
No. 1028-8P2 Base Plate

File Mark S&S

Extends 300"

Request Unit Pricing

Part No.	Part Name	Description	Unit
A 1302-2XM	Anchor only		1.00
A 1302-2XM	Anchor w/8 1/2" x 1 1/2" WS wood screws		1.50
A 1302-2XM	Anchor w/8 1/2" x 1 1/2" WS wood screws		1.50
A 1302-2XM	Anchor w/8 1/2" x 1 1/2" WS wood screws		1.50

▲ Stock Part. Includes 1 Min. proof load @ 2,500lb.
Note 2: Base plates may be required for installation.

64

Wood Purlin Anchor Kits

Package Contents No. 1302-2XM Kit

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P1 base plate
- 1 No. 1028-8P2 base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

Package Contents No. 1302-2XM Kit

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P1 base plate
- 1 No. 1028-8P2 base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

Package Contents No. 1302-2XM Kit

- 1 No. 1028 Swivel-D anchor
- 1 No. 1028-8P1 base plate
- 1 No. 1028-8P2 base plate
- 1 Set 5/8" x 1.14" set bolt
- 1 Set 5/8" x 1.14" set bolt

Request Unit Pricing

Part No.	Contents	Unit
A 1302-2XM	Anchor only	1.00
A 1302-2XM	Anchor w/8 1/2" x 1 1/2" WS wood screws	1.50
A 1302-2XM	Anchor w/8 1/2" x 1 1/2" WS wood screws	1.50
A 1302-2XM	Anchor w/8 1/2" x 1 1/2" WS wood screws	1.50

▲ Stock Part. Displacement parts under responsibility.

65

Standing Seam Anchor

No. 1028 Standing Seam Anchor is available in 3 lightweight aluminum. Base plate fits 18" panel seam width of 8.5" up to 26-1/2" wide. 3rd party tested to withstand a 5,000lb force in the specified load direction. Use with S&S No. 1028 seam clamp or No. 8511 RCT Seam Clamps for a wide range of standing seam profiles.

No. 1028 Specifications

- Min. tensile strength 5,000lb
- 3/8" grade 300 aluminum
- withstand static load of 100'
- Full range of metal panel profiles
- Factory seal report available on request

User Specifications

- Single person 300'
- HLL system full retention
- Compliance
- ANSI Z59.1-2017
- OSHA 1926.502

No. 1028 Request Clamps

- Deep-Lock system
- On-site formed seams
- Min. seam height 3/4"

Permanent or Temporary Anchor

Seam Clamp
Seam Clamp

No. 1028 Standing Seam Clamp

1 1/2" HDG Steel Plate
Torque Bolts (500/15)

Panel Width Adjustment

Seam Clamp
Seam Clamp

Request Unit Pricing

Part No.	Part Name	Seam Clamp	PPE Anchor	Unit
A 1028-1028	Anchor	12-1/2"	12-1/2"	1.00
A 1028-1028	Anchor	12-1/2"	12-1/2"	1.00
A 1028-1028	Anchor	12-1/2"	12-1/2"	1.00
A 1028-1028	Anchor	12-1/2"	12-1/2"	1.00

▲ Stock Part. Includes 5/8" x 1/4" or 2-3/4" attachment bolt.

66

Standing Seam Anchor

Panel Seam Width Specifications

When ordering, confirm the metal panel seam width and profile. No. 1028 RCT clamp will be required for seam profiles not compatible with No. 1028 clamps.

Panel Seam Width Compatibility

Base Plate Model	No. 1028-1028	No. 1028-1028	No. 1028-1028	No. 1028-1028
Clamp Profile	18-1/2"	18-1/2"	23"	26-1/2"
100' Retention	18-1/2"	18-1/2"	23"	26-1/2"
RCT Clamp	12-1/2"	12-1/2"	23"	26-1/2"

Anchor Attachment Holes

Anchor w/ 90° Bolt Hole
3/16" Dia. Hole
3/16" Dia. Hole

No. 8511 RCT Clamps

Extruded aluminum clamp designed to attach to many of the most common metal panel seam profiles. Clamps 3/8" wide. Requires 4 clamps. Visit www.superanchor.com for seam compatibility chart.

Request Unit Pricing Base Plate Only

Part No.	Part Name	Unit
A 1028-1028	Anchor	1.00
A 1028-1028	Anchor	1.00
A 1028-1028	Anchor	1.00
A 1028-1028	Anchor	1.00

▲ Stock Part. Includes 1 Min. proof load @ 2,500lb.
Note: Clamps include all required attachment bolts.

67

Standing Seam Anchor HLL Rigging Examples

Standing Seam HLL System

Standing seam HLL (horizontal and vertical) systems are identified for use with S&S and intermediate and HLL systems. HLL systems are identified for use with S&S and intermediate and HLL systems. HLL systems are identified for use with S&S and intermediate and HLL systems. HLL systems are identified for use with S&S and intermediate and HLL systems.

HLL Rigging Example w/5.0" Risers

HLL Accessories
HLL Accessories
HLL Accessories

HLL Rigging Example w/5.0" Risers and 4-Way Intermediate Anchor

Specified for HLL systems longer than 200' or where intermediate HLL is required.

HLL Accessories
HLL Accessories
HLL Accessories

HLL Loop Top / Pass-Thru Rigging Orientation

Way tops are specified for HLL intermediate and HLL systems. HLL systems are identified for use with S&S and intermediate and HLL systems. HLL systems are identified for use with S&S and intermediate and HLL systems.

HLL Accessories
HLL Accessories
HLL Accessories

68

Standing Seam Anchor VLL Rigging Examples

Standard VLL Rigging Example

Standing seam anchors used for HLL and HLL are positioned by raising both intermediate and HLL. Standing seam anchors used for HLL and HLL are positioned by raising both intermediate and HLL. Standing seam anchors used for HLL and HLL are positioned by raising both intermediate and HLL.

HLL Accessories
HLL Accessories
HLL Accessories

Intersecting HLL System

HLL Accessories
HLL Accessories
HLL Accessories

VLL Loop Top / Pass-Thru Rigging Orientation

Way tops are specified for HLL intermediate and HLL systems. HLL systems are identified for use with S&S and intermediate and HLL systems. HLL systems are identified for use with S&S and intermediate and HLL systems.

HLL Accessories
HLL Accessories
HLL Accessories

69