

Anchors D-Minus

The D-Minus™ is our most economical fall arrest anchor and is available in two models, 11 gauge 430 stainless steel or 11 gauge zinc plated powder coated steel. Installed with 6 nails or #12 screws, anchors are spaced between 8 and 12ft. Specified for use with asphalt shingle roofing, the low profile design is barely visible from the ground. The single piece fabrication does not use a D-ring, making it a "D-Minus". Great for new construction, or installed over the surface of existing asphalt shingles with our Retro-Fit flashing system.

Zinc plated steel anchor with gray powder coating



430 stainless steel anchor



D-Minus Anchor - 10 pack No. 1075

- 10pc 11 gauge zinc plated steel anchor with gray powder coating
- 60pc 3-1/4" length stainless steel spiral shank nails
- 10pc 7" butyl flashing strips
- English/Spanish labels and manuals

D-Minus Anchor - 10 pack No. 1075-S

Recommended for use in salt air environments.

- 10pc 11 gauge 430 stainless steel
- 60pc 3-1/4" length stainless steel spiral shank nails
- 10pc 7" butyl flashing strips
- English/Spanish labels and manuals



D-Minus - 80pc Bulk No. 1075-B

- 80 ea. 11-gauge zinc plated steel anchor with gray powder coating
- Order butyl flashings and fasteners separately



7" Butyl Flashing Strip - 80 pack No. 2043-D

- 80 ea. 7" peel and stick butyl flashings
- Bulk packaging

Specification of Use: Single person fall arrest.
Max User wt: 340lbs
Material: 11 gauge steel zinc plated and powder coated or 430 stainless steel
Min. Tensile Strength: 5,000lbs
Working Radius: 30 degrees
Engineering: 3rd party certified
Compliance: OSHA 1926:502, 1910.66
ANSI Z359.1-07, A10.32-2012

25