

# Anchors

## Apex Ridge Top



This anchor was developed specifically for production builders and roofing companies. It is installed directly over the roof decking and can be nailed down by the framing or roofing contractor. It eliminates the need to install a temporary anchor for fall protection thus saving time and money. The unique design allows the roofer to "course under" the tie-off tab with a full course of roofing material – no more cutting or notching the shingle to accommodate your safety anchors. The next course of roofing covers the anchor leaving the tie-off tab exposed. This is the only anchor on the market that allows the roofer to literally roof under/over without interrupting his install.

The APEX anchor is one of the lowest cost anchors available in the market. It is aesthetically pleasing and does not detract from the look of the roof. The APEX is powder coated in brown and blends in with most roofing materials but may also be painted to match the roofing color. Two APEX options are available: No. 2796 Ridge Mount anchor with two connector attachments and No. 2793 Hip Ridge anchor with one connector attachment.

- Device:** Fall Arrest Anchor
- Material:** 11-gauge steel
- Coating:** Zinc Coat & Powder Coat
- Install Hardware:** 304 stainless steel nails
- Min. Tensile:** 5,000 pounds
- Fall Indicator:** Stem Deformation
- Working Radius:** Direction of Slope or Leading Edge
- Specification Use:** 1 person Fall Arrest
- Max Weight:** 340 pounds with tools
- Instruction Manual:** English/Spanish/French
- Engineering:** 3rd Party Certified
- Compliance:** OSHA 1926:502, 1910.66,  
ANSI Z359.1-07, A10.32-2012

