

Tie-off Straps

Single D-Ring Tie-Off Straps

Supplied with a single D-ring and loop end these straps are designed for wrap webbing around cinching. Super Anchor Safety Hi-Viz™ Tie-Off Straps are mfg. with fluorescent color webbing for high visibility.

Standard Model Tie-Off Straps

Model	Length	Material	Tensile	A-end	B-end	wt/lb
3005-C	48"	2" Wide Orange Polyester	13,600lb	Slotted D-Ring	Loop	.5
3005-CB 50pc						39

High Visibility Tie-Off Straps

Model	Length	Material	Tensile	A-end	B-end	wt/lb
6048-GR48	48"	1-3/4" Hi-VizGR	7,425lb	Slotted D-Ring	Loop	.5
6048-H48		1-3/4" Hi-VizH™				

Value™ Single D-Ring Tie-Off Straps

Our most economical Tie-Off Strap mfg. with a flat D-ring

Model	Length	Material	Tensile	A-end	B-end	wt/lb
6050-D	36"	2" Yellow Polyester	13,600lb	Flat D-Ring	Loop	.75
6051-D	48"					1
6052-D	60"					1.25
6053-D	72"					1.5

Value™ Double Loop End Tie-Off Strap

Model	Length	Material	Tensile	A-end	B-end	wt/lb
6050	36"	Same as above		Loop	Loop	.5

Additional lengths available upon request.

No. 3005-C No. 6048-GR48™ Green Border No. 6048-H48 Orange Border No. 6050-D Value No. 6050 Value



SAS Hi-Viz™ Webbing

Loop End

PID labels w/date of mfg.

Loop End



Cinch Style

Flat D-Ring

Features

- Max. User wt 340lb
- ANSI/OSHA Compliant
- Zinc plated D-Rings
- English/Spanish Labels
- Inspection Label
- English/Spanish labels and manual

Inspection Labels

SAS Tie-Off straps have serial numbered inspection labels and a date entry for first use.

Serial Number: <input type="text" value="SAS"/>			
Número de serie: <input type="text"/>			
Date of First Use: <input type="text"/>			
Inspection			
MM	YY	By	Pass
<p>!WARNING TO USER! You are required to read and use the Instruction/Specification manual supplied at the time this device was shipped. Improper use and installation can result in serious injury or death. Follow inspection requirements before each use.</p>			

Unique Serial No.
User enters date of first use