

Anchors Safety Bar

Safety Bars are a Super Anchor Safety exclusive anchor that has been in service for over 15 years. Safety bars are designed for use with 2x wood trusses or steel framing members. Exact leg spacing can be used to stack trusses by linking several bars in series. The bar legs attach to trusses/chords easily with ball lock detent pins. Durable welded steel construction extends the service life of the safety bar.

- 2 Person Fall Arrest
- Exact leg center spacing
- Heavy Duty 1/8" steel construction
- Red powder coated
- 3/8" d. stainless steel ball lock detent pins w/shock cord tethers and stainless steel fittings
- 5,000lb min tensile strength
- Replaceable detent pins, tethers and labels.
- Compatible with Vertical Lifeline Systems and Self-Retracting Lifelines
- 3rd party certification for USA and Canada.

Complies with OSHA 1926:502/1910.66
ANSI Z359.1-07/A10.32-2012



Model	Top Chord	Leg Type	TC o.c. Length
1010	2x4	2ea "A" 1ea "B"	24x48
1011	2x6	2ea "C" 1ea "D"	24x48
1012	2x4+2x6	3ea "C"	24x48
1013	2x4+2x6+2x8	4ea "E"	24x48

Custom Models

1010-A	2x4	4ea "A"	24x72
1010-B	2x4	4ea "A"	16x48
1012-A	2x6	4ea "C"	24x72
1012-B	2x4+2x6	4ea "C"	16x48
1013-A	2x4+2x6+2x8	4ea "E"	24x72
1013-B	2x4+2x6+2x8	4ea "E"	16x48
1021	2x6+2x8+2x10	3ea "i"	24x48
1027	2x6 Metal C-Channel	3ea "K"	24x48

Leg Types:

Models 1010 and 1011, are fitted with an open end leg "B"/"C" that allow the 3rd truss to be rolled into position without lifting the safety bar.

Note: Custom design Safety Bars are available upon request. Specify top chord types, leg spacing and length. Bars are powder coated red unless otherwise specified.

36

Open
End
Leg