

# Lightweight Web Self-Retracting Lifelines

## Toss'R™ Type A SRL

Toss'R Self Retracting Lifelines (SRLs) are compact, durable, lightweight and may be used with overhead or horizontal anchor points. Use with a full body harness dorsal or side D-rings for fall arrest or work positioning. PID labels specify date of mfg., serial number and a space to enter the first use date. We call it the Toss'R because these units are not repairable if damaged in service or subjected to a fall.

### Toss'R No. 2990-A6

- Unextended unit length 18-1/2"
- 2.5lb wt. Including Steel Carabiner
- 6ft webbing length
- Ideal for small spaces, boom lifts or forklift attachments.



Polymer casing

Energy Absorber

Fall Indicator Inspection Label

Aluminum Auto-lock Carabiner

Steel auto-lock Carabiner

18-1/2" Length

20.0" Length

### Toss'R No. 2990-A11

- Unextended unit length 20"
- 3.5lb wt. Including Steel Carabiner
- 11ft webbing length



Ultra High Molecular Weight Polyethylene (UHMWPE) 4,500lb strength webbing



### Toss'R Model Features

- Steel auto-lock carabiner
- Swivel casing attachment
- 6kN Energy Absorber
- Fall indicator and inspection label
- Captive aluminum auto-lock carabiner
- English/Spanish labels and manuals
- Replaceable factory labels

### Performance Specifications:

Compliance: ANSI Z359.14-2012 Type A  
 Webbing: UHMWPE 19mm  
 Min. Strength: 4,500lb  
 Avg. Arrest force: 1,350lb  
 Max. Absorber length: 48"  
 Connectors: 3,600lb gate strength  
 User Wt. Range: 310-420lb  
 Max. Free Fall: 2ft

Model 2990-A6	<b>Toss'R™</b> 6ft(1.8m) Web Length
Lot mfg. Date 2018-03	Serial No. A-123456
First Use 2018-03	User enters date of first use

Compliance ANSI Z359.14-2012 Type A