

Fasteners • Detent Pins and Tethers

Detent Pins with Shock Cord Tether

Our high quality ball lock detent pins are furnished with outdoor rated elastic shock cord, mounting bracket and 2 fasteners. Swaged terminations are encased with heavy duty adhesive backed PVC shrink tube. Original equipment replacement specified for use with SAS fall protection devices.

- 3/8" Diameter grade 300sst
- 10,000lb Shear Strength
- Anodized aluminum grip
- Outdoor grade shock cord
- Aluminum swaged terminations w/Adhesive PVC shrink tube cover
- 430 sst tether bracket
- Includes tapping screw and button head bolt w/lock nut

Equipment Part No.	Fits Framing	Detent Pin Part No.	Length		
			▲ Pin	Cord	
1010 Safety Bar	2x4	2015-2.2-6	2.2"	6"	
		2015-4.4-6	4.4"		
1011 Safety Bar	2x6	2015-2.2-6	2.2"		
		2015-6.0-6	6.0"		
1012 Safety Bar	2x4/2x6	2015-2.2-6	2.2"		8"
1013 Safety Bar	2x4x6x8	2015-2.2-8			
1017 Joist Bar	4x2	2015-2.2-6			
2832 Truss Bar	2x4	2015-2.2-6			
2833 Truss Bar	2x4/2x6	2015-2.2-6			
1014 ARS	2x4-2x8	2015-2.2-6			
1215 SRL-UH	N/A	2015-6.0-8	6.0"	8"	
1097 Parapet		2015-2.9-4	2.9"	4"	

▲ Grip length. Note: the shaft length is longer.






Safety Bars

Truss Bars

Floor Joist Bars

Parapet Anchor

SRL-UH Holder



No. 2015-2.2-6
Pin Length 2.2"
Cord Length 6"

No. 2015-2.2-8
Pin Length 2.2"
Cord Length 8"

No. 2015-2.9-4
Pin Length 2.9"
Cord Length 4"

No. 2015-4.4-6
Pin Length 4.4"
Cord Length 6"

No. 2015-6.0-6
Pin Length 6.0"
Cord Length 6"

No. 2015-6.0-8
Pin Length 6.0"
Cord Length 8"

