

Mini-Max™ Kits

Mini-Max Kit

No. 4302

This kit features a 5 point harness with side D-Rings and tongue buckle leg straps that adjusts easily for different size workers. Perfect for applications where the harness may be tethered to the work platform or where workers may have to adjust the harness for different layers of outer wear. We also include a flex lanyard and carry bag. The Flex™ is a bungee type energy absorbing web lanyard with a rebar hook connector that will attach easily to many different size steel structures. Ideal for lift trucks, boom lifts, and work platforms where worker mobility is limited to a few feet. Can also be used for Horizontal Lifeline systems. Contents are placed inside the carry bag and shipped in a retail box.

Complies with ANSI Z359.13-2013/OSHA 1926.502 Fully assembled at our factory in Monroe, WA USA

Contents:


- No. TB-6067 Tongue Buckle sized 5 point harness with Super Anchor Safety Hi-VizHT™ webbing slotted dorsal and side D-Rings
- No. 6502 Flex energy absorbing lanyard with rebar hook + snap hook
- Gray carry bag with zipper closure and write-on personalizable name plate
- English/Spanish instructions and labels

Flex Specifications:

- Max. user wt. 310lb
- Max. Free fall 6ft
- 6ft fully extended service length
- 54" relaxed length
- 900lb max. arrest force
- *48" max. absorber deployment
- *10ft max. deployment length
- Rebar hook gate opening 2.6"

* Deployment lengths in the event of a free fall.

Tongue Buckle Leg Strap



Tongue Buckle Heavy Duty Grommets

Carry Bag



Write-on Personalizable Name Plate



Retail Box

No. TB-6067
Tongue Buckle
Harness



Snap Hook

Rebar Hook



No. 6502
Flex
Lanyard

Flex Lanyard Manual



English/Spanish
20 page manual

Mini-Max Kit Specifications

Kit No.	Size	Harness	Flex Model	Connectors	Kit/wt
4302-M	Medium 120-170	No. TB-6067 5 point with Hi-VizH webbing	No. 6502 Single Leg	"A" end Snap hook "B" end Rebar hook	8lb
4302-L	Large 150-310				