

Mini-Max™ Kits

Mini-Max Kit

No. 4303

This kit features our top of the line Deluxe Harness in 5 sizes and a Flex lanyard. Made with Tri-Lam3™ padding the deluxe harness provides a very comfortable full body harness that can be worn all day long. Contents are placed inside the carry bag and shipped in a retail box. Complies with ANSI Z359.13-2013/OSHA 1926.502 Fully assembled at our factory in Monroe, WA USA

Contents:

- No. 6101 Deluxe sized harness with Super Anchor Safety Hi-VizH™ webbing and 2 side D-Rings
- No. 6502 Flex energy absorbing lanyard with rebar hook + snap hook
- Gray carry bag with zipper closure and write-on personalizable name plate
- English/Spanish instructions and labels

Flex Specifications:

- Max. user wt. 310lb
- Max. Free fall 6ft
- 6ft fully extended service length
- 54" relaxed length
- 900lb max. arrest force
- *48" max. absorber deployment
- *10ft max. deployment length
- Rebar hook gate opening 2.6"

* Deployment lengths in the event of a free fall.



Side D-Rings

Flex Lanyard Manual



Mini-Max 4303 Kit Specifications

| Kit No. | Size | User/wt. | Harness | Flex Model | Connectors | Kit/wt. |
|---------|------------|----------|--------------------------------------|---------------------|---|---------|
| 4303-S | Small | 90-130 | No. 6101 Deluxe with Hi-VizH webbing | No. 6502 Single Leg | "A" end Snap Hook "B" end Rebar Hook | 10lb |
| 4303-M | Medium | 120-170 | | | | |
| 4303-L | Large | 130-220 | | | | |
| 4303-LL | Long-Large | 170-240 | | | | |
| 4303-X | X-Large | 240-340 | | | | |