

# Fall Protection Lifelines

## Labeling and Traceability

Product I.D. labels (PID) display ANSI, CSA and OSHA basic marking requirements. Each lifeline is serial numbered and provides a space for "First Use" date. A register of serial numbers is maintained to ensure traceability of the sale and material.

- Warning to consult instructions and perform inspection prior to each use
- Materials used, min. tensile strength and elongation specifications
- Part number and model type
- Date of manufacture (DOM)
- Origin and name of manufacturer
- User weight capacity
- Compliance standards
- Material type, diameter, and length
- Warning to avoid sharp edges
- Annual inspection requirement

**3 Strand Maxima Strength Rating**  
RESISTANCE D'UNE  
LIGNE DE VIE À 3 FILS  
Classification De 3  
Hébras De Force  
**10,582lb**  
**4,800kg**

**Model | MODELE | Modelo**  
PMP  
POL002

**Length | LONGUEUR | Largo**  
FL  
M

**Max. Elongation Wet or Dry**  
ETIREMENT MAX. (MOULLES/SECH)  
Elongación Máxima Mojado o Seco  
**1,800lb (8x) 8.2%**

**DOM / DF / FDF**  
YM-A/M

**Meets | CONFORME A | Cumple**  
ANSI Z39.1-07 / OSHA1926

**340lb (154kg)**

**Super Anchor Safety**

**Lifelines Matrix Label E0**  
CS00109-2017

Serial No. First Use Date entered by user

Inspection		
MM	YY	By

**Serial Number:** [Redacted]

**Date of First Use:** [Redacted]

**WARNING! Do not attach Rope Grab devices to the D-Ring of a body harness. An energy absorber or lanyard less than 30" (762mm) is required.**

**AVERTISSEMENT! NE PAS ATTACHER DE DISPOSITIF DE SAUVEGARDE À LA LIGNE DE VIE À L'ANNEAU EN D-SUR UN DOSSIER DE HARNAIS. UN ABSORBEUR D'ÉNERGIE OU UNE LIGNE DE VIE DE MOINS DE 762 MM (30 POUCES) SONT REQUIS.**

**ADVERTENCIA! No conectar los dispositivos de seguridad al anillo de D-Play. Requiere un amortiguador o accesorio de menos de 762 mm (30 pulgadas).**

**Super Anchor Safety**

**Lifelines Matrix Label E0**  
CS00109-2017

