

Lanyards and Connector Options

Lanyards with Carabiner Connectors

- 1" wide nylon
- Webbing Tensile Strength: 7,200lb(32.6kN)
- Aluminum Carabiner
- Min. Tensile Strength 5,000lb(23kN)
- Single Person Use: Max. wt. 340lb(154kg)
- English/Spanish Instruction label
- Inspection label
- Date of mfg. and serial no.

Compliance:
OSHA 1926.502/ANSI-Z359.1-07

72" Web Lanyard w/ Carabiner & Loop End

No. 6017
Pkg, Wt. 0.35 lb

60" Web Lanyard w/ Carabiner & Loop End

No. 6017
Pkg, Wt. 0.35 lb

48" Web Lanyard w/ Carabiner & Loop End

No. 6022
Pkg, Wt. 0.35 lb

24" Web Lanyard w/ Carabiner & Loop End

No. 6012
Pkg, Wt. 0.35 lb

18" Web Lanyard w/ Carabiner & Loop End

No. 6009
Pkg, Wt. 0.35 lb

See page 191 for Custom Web Lanyard Worksheet



Custom Lanyard Assembly

We offer custom fabricated web lanyards to your specifications, type of termination and connectors. Use our Custom Web Lanyard Worksheet in this catalog or visit our website to custom design your lanyard.



Webbing Specifications:

Part No.	Length	Tensile Strength
6033	18"	7,200lb
	24" or Longer	9,800lb
6034	Assembly Charge	

Note. Webbing unit cost is based on the service length

Custom Web Lanyard Connector Options

All connectors shown here comply with ANSI-Z359.12-09 and CSA Z259-12-11 for 3,600lb gate strength and 5,000lb min breaking strength.

On Custom Orders Specify Loop or Connector Type on Both "A" and "B" Ends

No. 5005-Z
Snap Hook



No. 5006-Z
Aluminum Carabiner



5001-Z
Steel Carabiner




No. 5008-Z
Rebar Hook



No. 5011
Lanyard D-Ring



No. 5009-Z
Swivel Snap Hook w/Fall Indicator



Red marker visible if subjected to a fall or other force

Min. activation force 500+/-75lb

Service Length w/Loop Ends

When a loop is specified for an "A" or "B" end the web length is calculated for a Carabiner connector length of approx. 5.0" Standard Finished Lengths: 18-24-36-48-60-72 [inches]