

Lanyards and Connector Options



No. 4108-8
8' Length

No. 4108-7
7' Length



No. 4108-6
6' Length



No. 4108-5
5' Length



No. 4108-4
4' Length



No. 4108-3
3' Length



No. 4108-2
2' Length



12 Strand Rope Lanyards

Rope lanyards are specified for use in work positioning and fall arrest. Rope lanyards can be looped around a tie-off point and are rated for use with steel I-Beams. Manufactured in the USA at our factory in Monroe WA.

Features

- Tenex 1/2" d. 12 Strand Rope USA mfg.
- 11,800lb tensile strength rope
- 3,600lb rated gate strength snap hooks
- Swaged terminations w/shrink tube cover
- Specification and inspection labels
- English-Spanish Instructions and Labels
- Complies w/ANSI Z359.1-07 OSHA 1926:502

3 Strand Rope Lanyards

Rope lanyards are specified for use in work positioning and fall arrest. Rope lanyards can be looped around a tie-off point and are rated for use with steel I-Beams. Manufactured in the USA at our factory in Monroe WA.



No. 4109-4
4' Length

No. 4109-RG4
4' Length

No. 4109-6
6' Length

No. 4109-RG6
6' Length

Features

- 5/8" d. 3 Strand Rope USA mfg.
- 9,300lb tensile strength rope
- 3,600lb rated gate strength rebar hook
- 4015-M Integral Adjuster rope grab
- Specification and inspection labels
- Swaged terminations with shrink tube covering
- English-Spanish Instructions and Labels