

Connectors • Snap Hooks • Rebar Hooks

Steel Double Locking Snap Hook

No. 5005-Z

Gate Strength	Proof Load	Min. Breaking	Net Wt.
3,600lb (16kN)	3,600lb (16kN)	5,000lb (23kN)	13.8oz

- The most common type of fall protection connector
- Forged Steel Zinc Plated
- 23kN Tensile Strength
- 21mm Gate Opening

Compliance:

OSHA 1926:502 ANSI-Z359.12-09/
CSA-Z259.12-11



Double Locking Swivel Snap Hook with Fall Indicator

No. 5009-Z

Gate Strength	Proof Load	Min. Breaking	Net Wt.
3,600lb (16kN)	3,600lb (16kN)	5,000lb (23kN)	17.6oz

- The most common type of fall protection connector
- Forged Steel Zinc Plated
- 23kN Tensile Strength
- 21mm Gate Opening

Compliance:

OSHA 1926:502 ANSI-Z359.12-09/
CSA-Z259.12-11



Double Locking Rebar Hook

No. 5008-Z

Gate Strength	Proof Load	Min. Breaking	Net Wt.
3,600lb (16kN)	3,600lb (16kN)	5,000lb (23kN)	27.8oz

- Forged Steel Zinc Plated
- 23kN Tensile Strength
- 65mm (2.55") Gate Opening

Compliance:

OSHA 1926:502 ANSI-Z359.12-09/
CSA-Z259.12-11



Double Locking Swivel Rebar Hook with Fall Indicator

No. 5002-Z

Gate Strength	Proof Load	Min. Breaking	Net Wt.
3,600lb (16kN)	3,600lb (16kN)	5,000lb (23kN)	33oz

- Forged Steel Zinc Plated
- 23kN Tensile Strength
- 65mm (2.55") Gate Opening

Compliance:

OSHA 1926:502 ANSI-Z359.12-09/
CSA-Z259.12-11



Fall Indicator Connectors

We offer 3,600lb gate strength snap hooks and rebar hooks with visual fall indicators. Designed to deploy when subjected to a free fall or other extreme force. The visible red indicator line is a quick identifier during inspection that that product needs to be immediately removed from service.

Fall Indicator In Service Position

Note: Rebar Hook 5002-Z will show a green color.



Fall Indicator Deployed

Note: Red is Visible

