

Connectors • D-Rings

D-Rings

Used primarily for harnesses, tie-off straps, lanyards and energy absorbers, our D-rings may be ordered separately or specified as a connector for custom assemblies.

Large D-Ring No. 5004

Proof Load	Min. Breaking	Net Wt.
3,600lb (16kN)	5,000lb (23kN)	4oz

Pkg, Wt. 0.2 lb

Compliance:
OSHA 1926:502 ANSI-Z359.
12-09/ CSA-Z259.12-11



Small D-Ring No. 5007

Proof Load	Min. Breaking	Net Wt.
3,600lb (16kN)	5,000lb (23kN)	4oz

Pkg, Wt. 0.2 lb

Compliance:
OSHA 1926:502 ANSI-Z359.
12-09/ CSA-Z259.12-11



Stamped O-Ring No. 5010-SM

The O-ring is for attaching class 1 connectors to wire rope horizontal lifelines and CRA-PT pass through tops.

- Zinc Plated Alloy Steel
- 1.4" I.D.
- Min. 5,000lb Tensile Strength

Compliance:
OSHA 1926:502 ANSI-Z359.
12-09 CSA-Z259.12



Lanyard D-Ring No. 5011

Proof Load	Min. Breaking	Net Wt.
3,600lb (16kN)	5,000lb (23kN)	4oz

Compliance:
OSHA 1926:502 ANSI-Z359.
12-09/ CSA-Z259.12-11

