CRO-4 HLL 4-Way Anchors

4.5"od. CRO-4 HLL Anchors

Specified for HLL end and intermediate anchors, that require bolt, field weld, or concrete embedment attachment to the supporting structure.



Specifications

- Min. tensile strength 5,000lb
- Compatible w/SAS HLL accessories
- Hot dip galvanized (HDG), 304sst or 316sst
- 3rd Party engineering by DH Glabe & Assoc. *Report available on request*
- Contact SAS sales team for custom mfg. and lead times

Compliance

ANSI Z359.18-17 Type A/T
CSA Z259.15:22 Type A/T
OSHA 1926.502

Ordering Information

- Order CRO-4 Model Size
- Order CRO 4-Way Top

CRO 4-Way Top

Part Name	Part No.	Type	Loop Top	wt/lb
▲ CRO 4-Way	1400-4WG	HDG	No.1093 Q345 steel	16

▲ *Stock Part includes attachment bolt pkg. and socket screws. Not available in stainless steel.*

CRO-4 Anchor



Request Unit Pricing

Riser Height	Part Name	Part No.	Material Type	4-Way ☐Top	Base Plate Inches	Anchor wt/lb	Riser ▲Sch
12	Δ CRO-4-12	1401-4G	■ HDG	No.1400-4WG	12x12x3/4 8 Hole	47	80 0.337 4.5"od.
		1401-4S	■ 304sst				
18	Δ CRO-4-18	1402-4G	■ HDG			62	
		1402-4S	■ 304sst				
24	Δ CRO-4-24	1403-4G	■ HDG			71	
		1403-4S	■ 304sst				
30	Δ CRO-4-30	1404-4G	■ HDG			79	
		1404-4S	■ 304sst				
36	Δ CRO-4-36	1405-4G	■ HDG			88	
		1405-4S	■ 304sst				

■ Standard Design Custom mfg. ▲ Nominal Dimension.
Δ Bolt, concrete embedment, expansion bolts or field welded.
☐ Order 4-Way top separately.
Note 1: Max. proof load 2,500lb.
Note 2: Backer plates may be required for installation.

Bolt Pkg.

1/2"x 7" 18-8sst
Attachment Bolt w/Lock Nut
Bonded SST Seal Washers