



SUPER ANCHOR SAFETY FALL PROTECTION

No.1095 Ladder LeashTM Tie-Off Strap for Ladders



Features

- 5,000lb tensile strength polyester webbing
- Zinc plated nail plate and cam buckle
- Installs into wood framing or thru asphalt roofing
- Single nail installation
- Reuseable nail plate
- Stabilizes ladder movement
- English/Spanish/French PID and inspection labels



Retail Package

Contents

- 2ea 1095 Ladder leashes
- 2ea 3" Spiral shank stainless steel nails
- English/Spanish instruction manual



Easy to Install/Easy to Remove

Sheathed Framing Installation



Wrap leash webbing around ladder leg between 2 rungs. Feed nail plate through loop end.



Position keyway over center of top chord a min. of 6.0" above the leading edge. Secure w/SAS supplied 3" sst nail through nail slot.



Pull leash webbing through cam buckle and cinch tight against the leading edge to prevent ladder movement.

Asphalt Shingle Installation



Position keyway over top chord center a min. of 6.0" above the leading edge.



Second course butt end overlaps keyway and conceals nail head. Waterproofing should be applied to the nail head after evacuation.



Gently strike the heel with a hammer to move the nail plate forward. The nail head will intersect the evacuation slot releasing the nail plate.

Durable Quality Construction
Designed for Reuse



Super Anchor Safety

17731 147th Street SE
Monroe, WA 98272
(425) 488-8868
www.superanchor.com

1095 Flyer 11-24 ©SCN [R]