SRL-BLE 2025 Manual Page B-39

## **Inspection Form B-2.0**

Ø

B

1

PID Labels

Aux. Labels

Shackle Yoke

38

35

This form to be completed by a Competent Person. It is recommended to include SRL-LE inspections as part of the owners safety program.



No.2991-LE10 SRL's are not serviceable. If one or both SRL was tagged UNUSABLE by the person inspecting SRL's fail any test or subjected to a fall, both units the SRL, an authorized person, or safety program must be removed from service and tagged "Unusable". administrator. WARNING! DO NOT use if only one SRL passes RL was returned to SAS for disposal. inspection. Model: 2991-LE10 

☐ **Enter Model not Listed:** Removed from Service Serial No. SAS Date of Mfg. Date of First Use: Date: **Owner** Company: Inspection By/ Date: Agency: Where Certificate Performed: No.: Pass Fail Inspection Page Part Name **Notes** Point В  $\overline{\mathbf{V}}$ |X|**WARNING!** Do not disassemble or attempt **Locking Test** 32 to repair an SRL. The 0 SRL Bracket 36 internal recoil spring can unwind when the casing 2 Shackle Swivel is opened resulting in serious injury or death. 8 Casing "Unusable" Tag 4 Casing Screws UNUSABLE 6 Cable Guide 35 **REMOVE SRL** 6 Cable Grip **FROM SERVICE** Date: 0 Cable Ø Cable Termination Use the original shipping box for units returned to 8 **Bracket Webbing** SAS for disposal. 34 9 **Energy Absorber** Serial No. 1 Visual Indicator 0 Rebardhook 37